



## All-in-One Transmitter IQ Pager Series

The All-in-One Transmitter is designed to work with JTECH's IQ pager series. It's easy for staff to use and durable for tough jobs.

The space-saving transmitter is an all-in-one solution for charging, transmitting and holding up to 15 pagers.

All-in-One Transmitter  
IQ Pager Charger with  
an Integrated Transmitter

### Additional Features

The All-in-One Transmitter is a space-saving solution for charging and transmitting to your GuestCall IQ pagers.

#### UHF Technology

Up to 2-mile range with unique ID to prevent signal interference.

#### Bright LED Display

Easy-to-read LED backlit digital display. Quick buttons make repeated communications a breeze.

#### Locate Feature

Easily locate missing pagers with a press of a button to reduce loss.

#### Durable Plastic

Built with high-quality materials for maximum durability and industry leading performance.

#### Smart Alerts

Out-of-Range and Search ensures guest contact and minimizes pager loss.

Call today for more information

800.321.6221  
www.jtech.com



# All-in-One Transmitter

## IQ Pager Series

### Specifications

<b>Display</b>	<ul style="list-style-type: none"> <li>&gt; 2 line display</li> <li>&gt; Blue LED backlit digital screen</li> <li>&gt; Water-resistant polyurethane</li> </ul>
<b>Interfaces</b>	<ul style="list-style-type: none"> <li>&gt; Serial: DB9- DCE (female) Connector</li> <li>&gt; Data Rates: 1200, 9600, 38400, 57600</li> <li>&gt; Characters: 8 Data Bits</li> <li>&gt; Stop Bits: 1</li> <li>&gt; Telco: RJ11 4-pin connector to PBX</li> </ul>
<b>Network</b>	<ul style="list-style-type: none"> <li>&gt; Interface: Ethernet 10Base-T</li> <li>&gt; Connector: RJ45</li> <li>&gt; Protocols: TCP/IP, ARP, ICMP</li> <li>&gt; Indicators (LED): Link &amp; Activity</li> <li>&gt; Management: SNMP, Telnet, Serial, Internal Web Server and Windows based utility for configuration</li> </ul>
<b>Electrical</b>	<ul style="list-style-type: none"> <li>&gt; Frequency range: 450 - 468 MHZ</li> <li>&gt; FCC Identifier: WDC</li> <li>&gt; IC Identifier: 7752A</li> <li>&gt; Channel Spacing: 12.5 KHz</li> <li>&gt; Speed / Baud Rate: 512/1200 bps</li> </ul>
<b>Power</b>	<ul style="list-style-type: none"> <li>&gt; DC 12V, 3.5A, SMPS</li> <li>&gt; RF Output (Watts): 2 Watts</li> <li>&gt; Format: POCSAG</li> </ul>
<b>Long Range Technology</b>	<ul style="list-style-type: none"> <li>&gt; UHF Frequency</li> <li>&gt; Unique System ID eliminates interference</li> <li>&gt; Exceptional site coverage</li> </ul>

### Dimensions

<b>All-in-One Transmitter</b>	Length: 8.75 inches (22.2 cm)	Width: 6.5 inches (14 cm)
	Height: 8.75 inches (22.2 cm)	Weight: 2.6 lbs (0.72 kg)



Call today for more information  
**800.321.6221**

### JTECH

1400 Northbrook Parkway  
Suite 320  
Suwanee, GA 30024, USA  
www.jtech.com  
Tel: (800) 321.6221



### About JTECH, an HME Company

JTECH is the largest onsite paging company in the world and the leading provider of onsite messaging solutions for hospitality, healthcare, retail, church nurseries and other markets. Headquartered in Suwanee, Georgia, JTECH is a wholly-owned subsidiary of HME, Inc., an innovative technology company focused on enhancing productivity and customer service for multiple markets including restaurant and pro audio since 1971.

©2017 JTECH, an HME Company logo and product names are registered trademarks of HM Electronics, Inc. All rights reserved.

PS17-TXAIO-v1

### IQ Pager Series



GuestCall IQ® Pager



QuietCall IQ® Pager

### You May Also Like:



StaffCall IQ®



Alpha-Numeric Pager



Rugged Pager