



IStation
Integrated Transmitter

IStation Integrated Transmitter

The IStation Transmitter is our most feature rich transmitter. Designed to work with JTECH apps like Host Concepts™ and SmartCall™ Messenger as well as popular 3rd-party solutions from QSR Automations, NCR Aloha, PAR, OpenTable® and MICROS.

IStation is network addressable and can easily integrate into your home-grown solution. It's fast, reliable and can manage up to 9999 pagers.

The optional TableScout can be used with the IStation to update table status and increase turnover.

Additional Features

The IStation is designed to integrate with other paging systems and software applications.

UHF Technology

Up to 2-mile rangewith unique ID to prevent signal space interference.

Restaurant Tough

Built with high-quality materials for maximum durability and industry leading performance.

Bright LED Display

Easy-to-read LED backlit digital display. Quick buttons make repeated communications a breeze.

Smart Alerts

Out-of-Range and Search ensures guest contact and minimize pager loss.

Manager, Staff & Guest Pagers

Supports the full line of JTECH pagers.

Multicast Feature

Extend your coverage by connecting multiple iStations.

Call today for more information

800.321.6221
www.jtech.com



IStation

Integrated Transmitter

Specifications

Display	<ul style="list-style-type: none"> > 2 x 3 inch 8 line display > Blue LED backlit digital screen > Water-resistant polyurethane
Interfaces	<ul style="list-style-type: none"> > Serial: DB9- DCE (female) Connector > Data Rates: 1200, 9600, 38400, 57600 > Characters: 8 Data Bits > Stop Bits: 1 > Telco: RJ11 4-pin connector to PBX
Network	<ul style="list-style-type: none"> > Interface: Ethernet 10Base-T > Connector: RJ45 > Protocols: TCP/IP, ARP, ICMP > Indicators (LED): Link & Activity > Management: SNMP, Telnet, Serial, Internal Web Server and Windows based utility for configuration.
Electrical	<ul style="list-style-type: none"> > Frequency range: 450 - 468 MHZ > FCC Identifier: WDC-ISTATION-N > IC Identifier: 7752A-ISTATION-N > Channel Spacing: 12.5 KHz > Speed / Baud Rate: 512/1200 bps
Power	<ul style="list-style-type: none"> > DC 12V, 3.5A, SMPS > RF Output (Watts): 2 Watts > Format: POCSAG
Long Range Technology	<ul style="list-style-type: none"> > UHF Frequency > Unique System ID eliminates interference > Exceptional site coverage

Dimensions

IStation Transmitter	Length: 9.37 inches (23.7 cm)	Width: 5.5 inches (14 cm)
	Height: 1.75 inches (4.3 cm)	Weight: 1.6 lbs (0.72 k)



Call today for more information
800.321.6221

JTECH

1400 Northbrook Parkway
Suite 320
Suwanee, GA 30024, USA
www.jtech.com
Tel: (800) 321.6221



About JTECH, an HME Company

JTECH is the largest onsite paging company in the world and the leading provider of onsite messaging solutions for hospitality, healthcare, retail, church nurseries and other markets. Headquartered in Suwanee, Georgia, JTECH is a wholly-owned subsidiary of HME, Inc., an innovative technology company focused on enhancing productivity and customer service for multiple markets including restaurant and pro audio since 1971.

©2017 JTECH, an HME Company logo and product names are registered trademarks of HM Electronics, Inc. All rights reserved.

PS17-TXIST-v1

Options



IStation Transmitter Keyboard



TableScout

You May Also Like:



Alpha-Numeric Pager



Host Concepts™



Waitlist & Messenger



SmartCall Messenger