







This cost effective extender pair uses HDBaseT technology to transmit HDMI signals from a single source (i.e., a cable or satellite set top box, Blu-Ray player, game console) over conventional CAT5e/6a over distances up to 230 feet (70 m). Each PoC-capable set is HDCP 2.2 compliant, supports 1080p and 3D, and provides bi-directional IR control to the room. The TX and RX units, powered by a single PSU at the TX side, each include a convenient LED power indicator.

- HDBaseT technology for uncompressed signal transmission
- Supports 4K x 2K, 3D, 1080p
- Transfers bidirectional IR control signals
- Up to 70 m (230 ft) transmission over CAT 5e/6a
- PoC technology (from TX to RX)
- LED power indicators
- HDCP compliant with EDID & CEC pass through
- 1 IR emitter and 1 IR adapter cable included

Technical Specificat	tions
Video	
TX Input	1 HDMI 1.4a
TX Output	1 RJ45, HDBaseT
RX Input	1 RJ45, HDBaseT
RX Output	1 HDMI 1.4a
Bandwidth	10.2 Gbps
Transmission	230 ft (70 m) over CAT 5e/ CAT 6a preferred
Max. resolution	Up to 4096 x 2160 @ 30 Hz
4K x 2K	Yes, up to 40 m over CAT 5e/ CAT 6a preferred
4K x 2K Supported formats	12 bit color depth, 4:2:2 color sampling @ 30 Hz 8 bit color depth, 4:4:4 color sampling @ 30 Hz
3D	Yes
HDCP 2.2	Yes
Audio	
Standards	HDMI 1.3c audio formats including Dolby TrueHD and DTS-HD
Set-up and control	
EDID	Yes
PoC	Yes, TX to RX
Ethernet	No
Bi-directional control	Yes, IR - 12V DC
General	
Power	100 - 240 VAC, 50/60 Hz
Operating voltage	12 V DC
Max. consumption	TBD
Temperature	14 to 104° F (-10 to 40° C)
Humidity	10 - 90% non-condensing
TX Dimensions	4.7"W x 1.0"H x 2.4"D (120 x 26 x 61 mm)
RX Dimensions	4.7"W x 1.0"H x 2.4"D (120 x 26 x 61 mm)
TX Weight (approx.)	.61 lb (.28 Kg)
RX Weight (approx.)	.61 lb (.28 Kg)

By making home technology simple, Clare provides exclusive benefits to integrators, builders, and homeowners. We offer innovative home automation solutions, Class D amplifiers, media distribution, controllable lighting, and IP CCTV components. For more information, visit clarecontrols.com.