

STANDARD FEATURES / CONFIGURATIONS

**Schlage Connect™
BE468**

Certification:	ANSI A156.36-2010 Grade 2
Product Dimensions: (wxhxd)	ext: 3"x 5"x 1" int: 3"x 8"x 2"
Weight:	
Warranty:	3 year electronics, limited lifetime mechanical & finish
Battery:	9V, 3AA
Latch Throw:	1"
Key & Cylinder:	2 keys, 5-pin, C keyway
Door Thickness:	1 ³ / ₈ " to 1 ³ / ₄ "
Cross Bore Distance:	5 ¹ / ₂ " center-to-center minimum
Cross Bore Diameter:	2 ¹ / ₈ "
Edge Bore Diameter:	1"
Backset:	2 ³ / ₈ " or 2 ³ / ₄ "
Faceplate Size:	1" x 2 ¹ / ₄ "
Faceplate Options:	Round corner, square corner, and drive-in (dual option standard)
Strike:	1 ¹ / ₈ " x 2 ³ / ₄ " round corners, strike reinforcer
Codes:	Pre-set, unique 6-digit programming code, two pre-set unique 4-digit access codes, 19 code capacity
Communications:	900 MHz (Z-Wave® RF)**
Operating Temps:	Ext: -30C to 66C Int: -10C to 49C

exterior

interior

FINISH CODES & DESCRIPTIONS

505	619	716
Lifetime Bright Brass	Satin Nickel (US15)	Aged Bronze

PACKAGING & CARTON SPECS

INDIVIDUAL CARTON

	CARTON WEIGHT	HEIGHT	WIDTH	DEPTH
BE468	3.8 lb	9.25 in.	5.125 in.	4.5 in.