


BERTOLINO® PORCELAIN FLOOR TILE & CERAMIC WALL TILE



Nocino Travertine 12 x 12 and 12 x 24 on floor. Corridor Vertical Pattern shown. Nocino Travertine 12 x 24 on wall. Brick Pattern shown.







BFRTOLINC PORCELAIN FLOOR TILE & CERAMIC WALL TILE

Matte Finish Porcelain Floor Tile







Crema Marfil

High Gloss Ceramic Wall Tile





Nocino Travertine

Nocino Travertine

Accents



Bianco Cararra Rope

Accents are high gloss.



Crema Marfil Rope



Nocino Travertine Chair Rail

Nocino Travertine Rope

PACKAGE INFORMATION

LOCATION

	18 × 18 Field Tile	(17-7/8" × 17-7/8" nominal size)	17.39 sq. ft. per carton						
	12×12 Field Tile	(11-13/16" × 11-13/16" nominal size)	10.55 sq. ft. per carton						
	12 x 24 Field Tile	(11-5/8" x 23-7/16" nominal size)	15.38 sq. ft. per carton						
	10 x 14 Field Tile	(9-27/32" × 13-3/4" nominal size)	11.62 sq. ft. per carton						
2 ½ x 12 Chair Rail									
	I x I2 Liner								

Suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed. Not recommended for residential pool decks.

Tile Thickness: on Grout Width 1/8" Floor on 1/16" Wall Grout Width:

Use of a latex modified thin-set is recommended for installation.

CLEANING PROCEDURES:

INSTALLATION INFORMATION

3/8"

· Remove loose dust and dirt with a damp cloth or sponge Use a neutral, non-abrasive cleaner suitable for ceramic tile

· Remove cleaning solution with a clean, damp sponge or mop

SHADE VARIATION

High (V3) change in color within each tile and from tile to tile. HIGH (V3)

Since there is shade variation in all fired ceramic and porcelain products, the tile and trim supplied for your particular installation may not match these samples. Color samples, as shown, may not be an exact product match. Mohawk expressly disclaims any liability resulting from product selections that rely solely upon color samples contained on this card. Final selection should always be made from actual pieces of tile and trim, not from tile and trim samples and/or color photo reproductions.

TEST DISCLOSURE INFORMATION

Wear Rating \square 2 3 4 5 9 Scratch Hardness 7 8 10 Resistance CHEMICAL IMPACT STAIN FROST

Slip Resistance (S.C.O.F) > 0.60 Wet (D.C.O.F) > 0.42 Wet

Wear Rating is based on a scale of 1 thru 5. 1 is recommended for light residential, 5 is Trated for heavy commercial usage. This is also known as PEI. Scratch Hardness is the measure to determine the relative hardness of glazes. This measure is also known as MOHs and uses a scale from 1 to 10 with 10 having the highest scratch hardness.



Look for our Reveal Imaging[™] products with Microban® for the ultimate in style and durability

REVEAL IMAGING[™]

Only stone is more real than Reveal. Every single tile looks virtually indistinguishable from natural stone, offering a clearly unique visual. The main attributes of state-of-the-art Reveal Imaging[™] technology. • Sophisticated state-of-the-art imaging.

- Unmatched color definition, detailing and veining.
- · Unparalleled emulation of natural stone.
- Pattern rarely repeats.

PRODUCT REFERENCE CHART

R	18 x 18	12 x 24*	2 x 2	3 x 3 Mosaic	3 x 12 Bullnose	10 x 14**	12 x 24**	3 x 12 Bullnose**	3 x 10 Bullnose**	2 x 12 Chair Rail	l x 12 Liner
Bianco Cararra	16157	16153	16149	16328	16238	16145	16144	16232	16235	16275	16276
Crema Marfil	16158	16154	16150	16329	16239	16164	16161	16233	16236	16277	16278
Nocino Travertine	16160	16156	16152	16330	16240	16166	16163	16234	16237	16279	16280
AVAILABLE TRIM											







N O T E S: Four 12 x 12 Field Tile were photographed together to show the High Shade Variation which is part of the natural beauty of this product. To achieve the maximum intended results, tile should be pulled from multiple cartons and placement decided upon prior to installation.

*3/16" recommended grout joints when square or rectangle sizes are used in staggered brick- joint pattern, where the overlaps do not exceed 33%