

GPS PVC Film

Product Description

GPS PVC Film is a window clear, premium grade film that is used for enclosures. It meets the requirements of the Consumer Products Safety Improvement Act (CPSAI) which restricts the use of Phthalates and Lead.



Features and Benefits

- ✓ Fire retardant, complies with the NFPA 701
- ✓ Contains low temperature additives for outdoor applications
- ✓ Contains UV stabilizers so this film can hold up against sun damage
- ✓ Easy to handle due to its low cohesion quality.
- ✓ It can be heat sealed

Roll Size			
THICKNESS:	16 MIL +/- 5%		
WIDTH:	54” + ¼” – 0”		
LENGTH:	71 YARDS		
NET WEIGHT:	100 LBS.* +/- 3%		
YARD YIELD:	.71		
Material Description			
FINISH:	SUPER DOUBLE POLISHED		
HAND:	SOFT – 3S		
COLOR:	CLEAR		
Special Features			
NON-PHTHALATE			
COMPLIANT NFPA701			
UV STABILIZED			
-10 COLD CRACK RATING			
Physical Properties			
Tensile Strength (PSI)	MD	2700	ASTM-D-882
	CD	2500	
Elongation (%)	MD	240	ASTM-D-882
	CD	260	
Tear Strength (Lbs./in)	MD	330	ASTM-D-1004
	CD	330	
Heat Shrinkage (%)	MD	-5	ASTM-D-1004
	CD	+2	
Shipped in a box, rolled in craft paper on 3” I.D. Cores			

GPS PVC Film

Roll Size			
THICKNESS:	20 MIL +/- 5%		
WIDTH:	54” + ¼” – 0”		
LENGTH:	58 YARDS		
NET WEIGHT:	100 LBS.* +/- 3%		
YARD YIELD:	.58		
Material Description			
FINISH:	SUPER DOUBLE POLISHED		
HAND:	SOFT – 3S		
COLOR:	CLEAR		
Special Features			
NON-PHTHALATE			
COMPLIANT NFPA701			
UV STABILIZED			
-10 COLD CRACK RATING			
Physical Properties			
Tensile Strength (PSI)	MD	2700	ASTM-D-882
	CD	2500	
Elongation (%)	MD	240	ASTM-D-882
	CD	260	
Tear Strength (Lbs./in)	MD	330	ASTM-D-1004
	CD	330	
Heat Shrinkage (%)	MD	-5	ASTM-D-1004
	CD	+2	
Shipped in a box, rolled in craft paper on 3” I.D. Cores			

*Shipping weight : Add 12 lbs to net weight.

Note: To the best of our knowledge, unless otherwise stated, these are typical property values and are intended as guides only, not as specification limits. Chemical resistance, odor transmission, longevity as well as other performance criteria is not implied or given and actual testing must be performed for applicability in specific applications and/or conditions. GLOBAL PLASTIC SHEETING MAKES NO WARRANTIES AS TO THE FITNESS FOR A SPECIFIC USE OR MERCHANTABILITY OF PRODUCTS REFERRED TO, no guarantee of satisfactory results from reliance upon contained information or recommendations and disclaims all liability for resulting loss or damage.



6020 Progressive Avenue, STE 300, San Diego, CA 92154

Toll Free: 866-597-9298 760-597-9298

Fax: 760-597-9574

Email: sales@globalplasticsheeting.com

www.globalplasticsheeting.com