## GPS Woven Coated HDPE 9, 12,16,24,30 mil

## **Product Description**

GPS Woven Coated HDPE is a woven coated HDPE scrim coated with prime LDPE coating resins. It has a very high strength-to-weight ratio and provides resistance to tears and punctures. A variety of thicknesses and colors are available in large custom sized panels. GPS Woven Coated HDPE is a perfect solution for cost effective applications.

## **Applications**

- ✓ Grain/Crop Covers
- ✓ Bulk Pile Covers
- ✓ Reserve Pits
- ✓ Frac Pits
- ✓ Under Rig Liners

- ✓ Retention Ponds
- ✓ Fresh Water Pits
- ✓ Flowback Pits
- ✓ Secondary Containment
- ✓ Aboveground Storage Tanks





6020 Progressive Avenue, STE 300, Vista, CA 92154 Toll Free: 866-597-9298 760-597-9298 Fax: 760-597-9574

> Email: sales@globalplasticsheeting.com www.globalplasticsheeting.com

## GPS Woven Coated HDPE 9, 12,16,24,30 mil

Manufactured In:



PROPERTIES	TEST METHOD	MINIMUM AVERAGE VALUES					
		9 MIL	12 MIL	16 MIL	20 MIL	24 MIL	30 MIL
WEIGHT	D5261	5.4 OZ/YD <sup>2</sup>	5.7 <b>OZ/YD</b> <sup>2</sup>	7.2 OZ/YD <sup>2</sup>	9.6 OZ/YD <sup>2</sup>	11.5 OZ/YD <sup>2</sup>	13.4 OZ/YD <sup>2</sup>
THINKNESS		9 MIL	12 MIL	16 MIL	20 MIL	24 MIL	30 MIL
GRAB TENSILE (LBS.)	D751	MD 200 CD 135	MD 210 CD176	MD 230 CD 210	MD 330 CD 286	MD 352 CD 300	MD 352 CD 300
MULLEN BURST	D6241	300 PSI	350 PSI	400 PSI	600 PSI	680 PSI	780 PSI
ACCELERATED UV WEATHERING	D4355	>80% AFTER 2000 HRS EXPOSURE	>90% AFTER 2000 HRS EXPOSURE				
STANDARD ROLL DIMENSIONS							
ROLL LENGTH <sup>(2)</sup> , FT		3,000	3,000	4,000	3,000	2,250	2,250
ROLL WIDTH <sup>(2)</sup> , FT		12	12	12	12	12	12
ROLL AREA, FT <sup>2</sup>		36,000	36,000	48,000	36,000	27,000	27,000

<sup>(1)</sup> 9 of 10 views shall be Category 1 or 2. No more than 1 view from Category 3.

 $^{\scriptscriptstyle (2)}\mbox{Roll}$  widths and lengths have a tolerance of +/-  $1\,\%$ 

Custom material thicknesses also available

This data is provided for informational purposes only. Global Plastic Sheeting makes no warranties as to the suitability or the fitness for a specific use or merchantability of products referred to, no guarantee of satisfactory results upon contained information or recommendations, and disclaims all liability from resulting loss or damage. This information is subject to change without notice, please check with Global Plastic Sheeting for current updates.



6020 Progressive Avenue, STE 300, Vista, CA 92154 Toll Free: 866-597-9298 760-597-9298 Fax: 760-597-9574

> Email: sales@globalplasticsheeting.com www.globalplasticsheeting.com