

Ultra Perm Tape

Waterproof Sealing & Patching Aggressive Tape

Ultra Perm Tape is an exceptionally aggressive all weather tape that is VOC free, stable from 70° F to 200°F. It sticks to virtually anything. Remove the release liner and place by hand, or use a hand roller to apply the tape to irregular surfaces. It can be used **underwater** or on the **roof**. It is that **STRONG** and Versatile!

- VOC Free
- Stable from 70 degrees to 200 degrees F.
- Quadruple Thick Adhesive- so strong it can't be ripped by hand
- Grips all kinds of surfaced including rough, uneven or smooth surfaced
- EDM, TPO and Metal Roof Patching
- Loves extreme roof temperatures
- Flexible
- 26 mil thick
- 15 lbf/in strength
- Resistant to UV light
- EDM, TPO, Metal Roof Patching
- *****Warning: Don't put it down and expect to remove it, as it won't come up! *******

Property	Typical Value	Test Method
Thickness w/o liner	26 mils	ASTM D1777
Tensile Strength	15 lbf/in	ASTM D882
Elongation	>700%	ASTM D882
Adhesion	20 lbf/in	ASTM D882
25° Peel Adhesion	13 lbf/in	PSTC-1
150° Peel Adhesion	2.2 lbf/in	ASTM D6862
WVTR @ 73°F/50%rh	<0.02 b/100in ² /24hrs	ASTM D6862
Permeance @ 73°F/50%RH	<0.005 perms	ASTM E96-B
Low Temperature Flexibility	High	ASTM E96-B
Application Temperature	20°F to 170°F	ASTM D1970
W/ Recommended Primer	-25°F to 25°F	
Service Temperature	-70°F to 200°F	
Shelf Life	5 years	
Color	Black	

Note: The above value represents average laboratory results. Each user should evaluate the tape to determine the suitability for each and every application and shall assume all risks and liability connection therewith.