

4-Axis Center-Drive Lathes Specifications

	CTR-354	CTR-504	CTR-654	CTR-854
WORKHOLDING	3.50" COLLET	5.00" COLLET	6.50" COLLET	8.50" COLLET
SPINDLE BORE	3.53"	5.03"	6.53"	8.75"
ROUND BAR CAPACITY	3.50"	5.00"	6.50"	8.50"
SPINDLE CENTERLINE HEIGHT	46.00"	46.00"	46.00"	46.00"
MAX OD TURNING LENGTH	9.00"	9.00"	9.00"	9.00"
MAX ID BORING DEPTH	8.88"	8.88"	8.88"	8.88"
MAX TURNING DIAMETER	15.00"	15.00"	15.00"	15.00"
CNC CONTROL	FANUC 30i-SERIES	FANUC 30i-SERIES	FANUC 30i-SERIES	FANUC 30i-SERIES
SPINDLE SPEED RANGE (STD)	35-3,000-RPM (BELT)	35-2,500-RPM (BELT)	35-2,000 RPM (BELT)	35-1,600 RPM (BELT)
SPINDLE DRIVE	FANUC ALPHA HVi	FANUC ALPHA HVi	FANUC ALPHA HVi	FANUC ALPHA HVi
SPINDLE HORSEPOWER (STD)	30-HP CONTINUOUS	30-HP CONTINUOUS	30-HP CONTINUOUS	30-HP CONTINUOUS
SPINDLE HORSEPOWER (OPT)	40-HP CONTINUOUS	40-HP CONTINUOUS	40-HP CONTINUOUS	40-HP CONTINUOUS
SERVO DRIVE SYSTEM	FANUC ALPHA HVi	FANUC ALPHA HVi	FANUC ALPHA HVi	FANUC ALPHA HVi
	AC DIGITAL	AC DIGITAL	AC DIGITAL	AC DIGITAL
MAX AXIS FEED RATE	200-IPM	200-IPM	200-IPM	200-IPM
MAX AXIS TRAVERSE RATE	400-IPM	400-IPM	400-IPM	400-IPM
X-AXIS (X1 & X2) TRAVEL	7.88"	7.88"	7.88"	7.88"
Z-AXIS (Z1 & Z2) TRAVEL	9.00"	9.00"	9.00"	9.00"
TURRET STATIONS	12-STD 15-OPT	12-STD 15-OPT	12-STD 15-OPT	12-STD 15-OPT
INDEX SYSTEM	BI-DIRECTIONAL	BI-DIRECTIONAL	BI-DIRECTIONAL	BI-DIRECTIONAL
	SKIP-INDEX	SKIP-INDEX	SKIP-INDEX	SKIP-INDEX
	INDEX ANYWHERE	INDEX ANYWHERE	INDEX ANYWHERE	INDEX ANYWHERE
	SERVO-INDEX,	SERVO-INDEX,	SERVO-INDEX,	SERVO-INDEX,
	HYD CLAMP	HYD CLAMP	HYD CLAMP	HYD CLAMP
TOOL SHANK SIZE (STD)	1.00" x 5.00"	1.00" x 5.00"	1.00" x 5.00"	1.00" x 5.00"
MAX BORING BAR DIAM	2.50"	2.50"	2.50"	2.50"
LIVE TOOLING HP (OPT)	10-HP	10-HP	10-HP	10-HP
LIVE TOOLING TORQUE	795 IN-LB CONT	795 IN-LB CONT	795 IN-LB CONT	795 IN-LB CONT
LIVE TOOL COLLET SIZE	ER40 (1.181")	ER40 (1.181")	ER40 (1.181")	ER40 (1.181")
ELECTRICAL POWER	460-VAC 3-PH 60-HZ	460-VAC 3-PH 60-HZ	460-VAC 3-PH 60-HZ	460-VAC 3-PH 60-HZ
	75-KVA	75-KVA	90-KVA	90-KVA
COOLANT CAPACITY	80-GAL	80-GAL	80-GAL	80-GAL
MACHINE HEIGHT	94.00"	94.00"	94.00"	94.00"
FLOOR SPACE	130"-W x 165"-LG	161"-W x 275"-LG	161"-W x 275"-LG	161"-W x 275"-LG
SHIPPING DIMENSIONS	96"-W x 165"-LG x 94"-H	96"-W x 165"-LG x 94"-H	96"-W x 165"-LG x 94"-H	96"-W x 165"-LG x 94"-H
MACHINE WEIGHT	42,000-LBS	44,000-LBS	44,000-LBS	45,000-LBS

BARDONS & OLIVER

5800 HARPER ROAD • SOLON, OH 44139 USA
 PHONE: 440-498-5800 FAX: 440-498-2001
www.bardonsoliver.com