

Bluetooth Printer



Printing Method	Direct thermal
Printing Speed	160mm/s, 200mm/s, 230mm/s, 260mm/s
Black Mark Detection	Support
Network Monitoring	Support
Roll Paper	Paper Width: 79.5 ± 0.5mm Diameter:83mm
Column Capacity	576 dots/line or 512 dots/line
Character Size	ANK, Font A: 12x24 dots Font B: 9x17 dots
Command	Compatible with ESC/POS
Interface (optional)	Serial/Parallel/USB/LAN, USB+ Serial
Auto Cutter	Full or Partial (optional)
Reliability	Printing head Life: 100 km
Bar Code	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/ CODE93/CODE128
Paper Thickness	0.06 - 0.08mm
Adaptor Input Voltage	AC 110V/220V, 50-60Hz
Power Supply	DC 24V -2.5A
Printer Inout Voltage	DC 24V -2.5A
Cash Drawer Control	DC 24V -1A
Working Environment	Temperature (0-45° C), humidity (10-80%)
Storage Environment	Temperature (-10-60° C), humidity (10-80%)
Drivers	Win 9X/Win 2000/Win 2003/Win XP/Win 7/win 8/WIn 10/Linux