

TKM CeraPrint®

Made in Germany

The ceramic particle coated doctor blade has an outstanding durability and reliability attributes.

Due to the latest coating technologies, TKM Meyer is able to apply an extremely homogeneous layer structure onto the blade surface. This provides TKM CeraPrint exact coating parameters for you to achieve consistent and reproducible printing results even on difficult printing jobs.

This new, highly wear-resistant coating avoids corrections of the blade angle and blade pressure during the printing process, resulting in significantly higher durability of the doctor blade and print cylinder.

Advantages

- State-of-the-art coating technology
- Reduces hazing and streaking
- Reduces machine downtimes
- High doctor blade durability at low blade pressure
- Avoids waste
- Suitable for medium and large printing jobs
- highly reliable and reproducible printing results even at gradients and halftones
- Suitable for all inking systems
- Safety for the operator during the entire printing process

Doctor blade shape

Applications

Lamella



Gravure and flexographic printing

Stable 2°



Gravure and flexographic printing

FlexoTip



Flexographic printing

Detailed dimensions

A (doctor blade width)	10.0 mm	–	60.0 mm
B (doctor blade thickness)	0.15 mm	–	0.3 mm
C (tip thickness)	0.055 mm	–	1.5 mm
D (tip width)	1.0 mm	–	1.7 mm

TKM Meyer is certified according to the following standards:

DIN ISO 9001 | DIN ISO 14001 | DIN ISO 5001

info@tkmmeyer.com
www.tkmmeyer.com