



IN THE BUSINESS OF YOUR SUCCESS®

ADP® 700 Timeclock for Small Business

ADP offers an **affordable, feature-rich data collection solution** for use with ADP's time and attendance software. Whether you want to help control buddy punching or collect employee data more efficiently, the ADP 700 Timeclock is right for you.

FLEXIBLE AND EASY TO USE

Designed for small businesses, the compact ADP 700 Timeclock comes complete with everything you need to quickly install the clock, including power supply, wall mount and screws, cabling and 25 badge cards (for proximity or barcode reader clocks).

The keypad features text-based function keys or icons for common tasks such as department/ job transfers, clocking out for lunch, entering tips and recalling the last punch time, enabling ease of use, faster adoption and enhanced employee satisfaction.

ADP configures the clock to your specific requirements so you can get started quickly and easily.

TIMEKEEPING MADE EASY

The ADP 700 Timeclock:

- Can prevent repeated punches
- Automatically adjusts for daylight saving time
- Fully integrated with ADP Time & Attendance software to eliminate manual data entry and potential errors
- Hidden wiring helps prevent vandalism
- Battery backup for reliable operation

FEATURES

Bar code or proximity badge entry

PIN entry

Biometric finger scan

Touch screen display

Ethernet or serial communication

Optional Wi-Fi communication



ADP 700 Specifications

- Screen Display 7" Widescreen Capacitive Touch Display – 800 x 400 Resolution
- Enclosure PC-ABS
- Dimensions H 10.5" x W 9" x D 4"
- Clock Battery-backed real-time clock, 12 or 24-hour format, USA or international, quartz precision
- Memory 128MB RAM / 8GB Flash (SD card)
- Weight Terminal = 2.884 lbs. / 1.308 KG
Shipped = 5 lbs. / 2.268 KG
- Power 12 VDC (nominal) 1.25A, 15W maximum
- Optional uninterruptible power supply with charger
- Optional Battery Backup Type = NiMH, ranges from 1.5 hours (with bio) to 4 hours (without bio)
- Direct Connect – Standard 50' RS-232 serial communications cable included; optional 100' or 250' cable available
- Ethernet – Includes 7' 10/100Base T connection for connection to the Ethernet network TCP/IP protocol for communication for the host PC timeclock
- Numeric keypad, 0-9
- Four predefined function keys
- Clear/Enter keys
- Biometric Sensor Made by Suprema with a 508dpi capacitive sensor from UPEK (algorithms are proprietary)
- Proximity Sensor HID Support
- Frequency = 125 khz
- Format = Sensor 2601, 26 bit
- Environment Operating temperature: 0° to 50° C (32° to +122° F)
- Storage temperature: -20° to 80° C (-4° to +176° F)
- HTTPS service capable
- Preset common host address
- Diagnostics On-board diagnostics
- Interface Standard 802.3 10/100BASE-T Ethernet with DHCP
- Optional internal modem (FCC Part 68 certified)
- Certifications CE Mark, FCC Part 15 Class A, RoHS

Specifications subject to change without notification