KLARITY 8 MULTI-PURPOSE LOUDSPEAKER



The Klarity 8 is a high performance, self-powered, 2-way multipurpose loudspeaker. It is suitable for standalone music and speech applications, or to be used as reinforcement in larger installations. Combined with the Klarity 18 subwoofer, this small, powerful cabinet can achieve high SPLs, setting a new precedent for output from a compact design. A rotatable 90° x 60° constant directivity horn ensures even, predictable coverage across the entire listening area, with the additional flexibility of a rotatable design. The integral high efficiency class-D amplifier maximizes ease of use in a wide variety of applications, making the Klarity 8 a suitable candidate for both portable and installed applications. The high-grade, void-free Baltic birch cabinet is finished with a tourgrade, high-impact EXL Polyurea coating that outlasts standard painted cabinets by years.

FEATURES

- Premium quality transducers
- High-grade void-free Baltic birch construction
- High efficiency class-D amplification
- Full power intelligent limiting
- 90° x 60° aluminum rotatable horn flare
- M8 rigging for suspension
- 4 selectable DSP configurations
- 12 gauge powder coated heavy duty grill
- Tour-grade high-impact EXL Polyurea
- Powercon locking power cable

SPECIFICATIONS

| PURPOSE | 2-WAY TRAPEZOIDAL |
|--|---|
| Low Frequency | 8" Cone Transducer |
| High Frequency | 1.75" Titanium Compression Driver |
| Amplifier | 700W Class-D |
| Operating Frequency +/-10dB | 44Hz - 20KHz |
| Free Field Response +/-3dB | 56Hz - 18KHz |
| Maximum SPL (note1) | 129dB |
| Coverage Pattern | 90° x 60° Rotatable |
| Audio Input | Balanced XLR |
| Audio Through | Balanced XLR |
| Transducer Protection | Thermal & Excursion Limiting |
| Amplifier Cooling | Temperature Controlled Fan |
| DSP Presets | 1. Full Range 2. 90Hz HP 3. Vocal 4. Mic Level Input |
| AC Power Input | Powercon |
| Input Voltage | Auto-switching 100 - 250V |
| AC Power Consumption 1 / 8 Power (110V / 220V) Amps | 1.2 / 0.6A |
| Material | High-Grade Void-Free Baltic Birch |
| Finish | Tour-Grade High-Impact EXL Polyurea |
| Grill | 12 Gauge Powder Coated Steel |
| Rigging | M8 Rigging for Suspension |
| Dimensions DxWxH (inches) | 9.8 x 9.5 x 18.1 |
| Dimensions DxWxH (mm) | 250 x 240 x 460 |
| Weight (lb) | 28.2 |
| Weight (kg) | 12.8 |

NOTE: (1) Max. SPL 1W / 1m with 4dB crest factor pink noise

APPLICATIONS

- Night Clubs & Lounges
- Mobile DJs
- Live Music
- Corporate Facilities
- Speeches & Public Address
- Restaurants & Cafés
- Houses of Worship
- Delay & Other Coverage

WWW.PKSOUND.CA

```
US OFFICE • 415.845.0132
580 Eccles Ave S. San Francisco, CA. USA. 94080
```