

**1** Outdoor SMB kit

x4 8 x 25  
x4 8 mm washer  
x4 T8 x 25  
x4 M8 x 25

Desiccant

T10

x2 T3 x 8  
x2 T3 x 8

x3 T4 x 25  
x3 T4 x 25  
x7 M4 x 8

**2**

1

2

x3

Desiccant

Reset

microSD card

**3**

A

M20

B

4/3-in. NPT

C

**4**

O-ring

**5**

60 x 40 mm

FRONT

Ø6 mm

T3 x 8 x4

40 mm

60 mm

x4

**6**

A

M8 x4

B

M8 x4

**7**

12VDC

RJ45 Ethernet (PoE)

12 VDC SELV Class 2

7 mm (0.3 in)

24-28 AWG

Default: DHCP on (no DHCP: 192.168.0.1)

This equipment is only to be connected to PoE networks without routing to outside plant

**8**

x2

**9**

x3

**1** IPHelper



<http://downloadstore.boschsecurity.com/>




**2** Configuration >> Camera >> Installer Menu

Installer Menu

Base frame rate: 15 fps

Mirror image:  On  Off

Flip image:  On  Off

Calibration

Type: Mount position

Mount position: Ceiling

Tilt [deg]:

Roll [deg]: 0

Elevation [m]:

Set

Reboot device: Reboot

Factory defaults: Defaults


**3** View & Configure



<http://downloadstore.boschsecurity.com/>

↓ ↓ ↓

Bosch Video Client    Video Security Client    Configuration Manager





**FLEXIDOME IP panoramic 5000 MP**  
NUC-52051-F0E



**Quick Installation Guide**

Bosch Security Systems B.V.  
Torenallee 49  
5617 BA Eindhoven  
The Netherlands  
[www.boschsecurity.com](http://www.boschsecurity.com)  
© Bosch Security Systems B.V., 2015

