

# Fusion Interleaf Flap Disc

The combination of a premium coated abrasive layer over non-woven surface conditioning material is what makes Fusion a superior flap disc. Fusion easily blends and finishes welds in one operation. Grain size is calibrated in order to match a #4 finish.

## METALS

Stainless steel - Aluminum - Mild steel - Brass

## PRODUCT FEATURES

Blends and finishes stainless steel in one step  
Matches a satin finish  
Very controlled weld grinding  
High quality finish

## APPLICATIONS

Blend corner welds on stainless steel railings  
Blend small TIG welds on stainless steel kitchen equipment

## SPECIFICATIONS

Grain Types  
Aluminum Oxide


Grain Sizes  
Coarse, Medium, Very Fine

## AVAILABILITY

DIAMETER X ARBOR		MAX RPM	OPTIMUM RPM	CRS	MED	VFINE
inch	mm					
4-1/2 x 7/8	115 x 22.2	13,300	2,700-5,000	894000	894001	894002
4-1/2 x 5/8-11	N/A	13,300	2,700-5,000	894003	894004	894005
5 x 7/8	125 x 22.2	12,200	2,500-4,500	894006	894007	894008
5 x 5/8-11	N/A	12,200	2,500-4,500	894009	894010	894011

## TIP

While working on stainless steel with a satin finish, run this product in the same direction as the scratches to match the grain.



800-225-8182  
www.rexcut.com  
info@rexcut.com

youtube.com/user/rexcutabrasives  
twitter.com/rexcut  
linkedin.com/company/rexcut  
facebook.com/rexcut

**an employee owned company**



Improve Your Daily Grind