

Step 1- Finding out what version your Mac is

Select the Apple icon 🗰 about this Mac



Step 2- Finding out the I.P address of your Canon device

Go to your Canon machine and select

- Settings/Registration button
- Preferences
- Network
- Output Report
- Do you want to print the User data list (Yes)

The machine will print out a 3 pages User Data List, on this you will find your machine's I.P address.

Step 3 - Downloading Drivers and Downloads

Go to the Canon website

https://www.canon.com.au/en-AU/Business/Support/Drivers-and-Downloads



d your product		_	_	
nave selected drivers and downloads				Type in and select your
020			Q	device model
				\mathbf{V}
nageRUNNER IR2020 IR ADVANCE C2020				
Calloll Explore Products Support Business			8 7 0	
DRIVERS & DOWINLOADS		Search driv		
		Search dra		
DRIVERS & DOWNLOADS PHODUCT PAGE	OS version: All	Sourch div		Select the
DRIVERS & DOWNLOADS PRODUCT FASS	OS version: All For Windows	Search day		Select the version of Mac O/S
DRIVERS & DOWNLOADS PRODUCT PAGE Filter by: Drivers Categories: Everything Windows Mac Linux Unix			~ Q	Select the version
DRIVERS & DOWNLOADS PRODUCT PAGE Fitter by: Drivers Categories: Everything Windows Mac Linux Unix [Windows 2000] Raster/PCL5e Fax Driver Version 8:70	For Windows	Updated	107 Q	Select the version of Mac O/S

Step 4- Select the 'UFR' Printer Driver

(If you have purchased 'PostScript' download the PS Printer Driver)

	UFR II/U	JFRII LT Printer Driver & Utiliti	<u>ies for Macintosh V10.8.1 [Intel</u>
	printer con		Mac OS X 10.5 - 10.11 Caution If you add a [Internet Printing Protocol - IPP] may be selecte
	http://s	support-au.canon.com.au/contents/AU/EN	N/0100491502.html
Downlo I have Downloa	e read and understood the	e information above, and wish to download the o	designated software.
ep 5	×	Mac_UFRII_Ver1070_00 2 items	-0
		UFRILLT_LUPS_LX_Installe r.pkg may find the installer app wnloads folder.	Double click on the installer
	Mac_UFRII_Ver1070_	00	

Step 6- Click continue through each window





www.thebmsgroup.com.au

Step 7 - Continue clicking on prompted icons

000	Install Canon UFR II/UFRII LT/LIPSLX Printer Driver	
 Intro Lice Dest Insta Insta 	To continue installing the software you must agree to the terms of the software license agreement. Click Agree to continue or click Disagree to cancel the installation and quit the Installer. Read License Disagree Agree and i or fing	
Summa	READ CAREFULLY AND UNDERSTAND ALL OF THE RIGHTS AND RESTRICTIONS DESCRIBED IN THIS AGREEMENT BEFORE INSTALLING THE SOFTWARE. BY CLICKING THE BUTTON INDICATING YOUR ACCEPTANCE AS STATED BELOW OR INSTALLING THE SOFTWARE, YOU AGREE TO BE BOUND BY THE TERMS AND CONDITIONS OF THIS AGREEMENT. IF YOU DO NOT AGREE TO THE FOLLOWING TERMS AND CONDITIONS OF THIS AGREEMENT, DO NOT USE THE SOFTWARE. 1. GRANT OF LICENSE Canon grants you a personal, limited and non-exclusive license to use ("use" as used herein shall include storing, loading, installing, accessing, executing or displaying) the SOFTWARE solely for the use with Products only on computers directly or via	
	Print Save Go Back Continue)





Step 8 -In the top right hand corner select 💣 'System Preferences'

•••	< > ===		System P	references		Q Search	8
General	Desktop & Screen Saver	osee Dock	Mission Control	Language & Region	Security & Privacy	Spotlight	Notifications
CDs & DVDs	Displays	Energy Saver	Keyboard	, Mouse	Trackpad	Printers & Scanners	Sound
iCloud	(@) Internet Accounts	Extensions	Network	Bluetooth	Sharing		
Users & Groups	Parental Controls	App Store	Dictation & Speech	Date & Time	Startup Disk	Time Machine	Accessibility

Step 9 -Click on the plus sign that is indicated below

$\bullet \bullet \circ \checkmark \blacksquare$	Printers & Scanners	Q Search
Printers 192.168.1.240 • Idle, Default 192.168.1.248 iRADC • Idle 192.168.1.50 • Idle 192.168.1.50 • Idle Image: Straight of the straight		supplies C5235/5240
†	Default printer: 192.168.1.2 Default paper size: A4	240 •

Step 10 - Select IP. Enter the I.P address of your Canon Device into the Address Field E.g 192.168.1.240. Leave Protocol as LPD

	_	Add	Q Search	
Default IP V	lindows		Search	
Address:	Enter host name or IF	address		
Protocol:	Line Printer Daer			٢
Queue:	Leave blank for defau	ilt queue.		
Name:				
Location:				
Use:				٥
				Add

Step 11 - Adding Print Software

(Before closing the I.P address window) - at the bottom of the window, click 'Use' and select 'Select Sofware' to select the model of your device. Then press OK.

	Q Canon	0
	0000	
Canon iR-ADV C350		
Canon IR-ADV C350 F	s	
Canon iR-ADV C351		
Canon iR-ADV C351 F	s	
Canon iR-ADV C5030	/5035	
Canon IR-ADV C5030	/5035 PS	
Canon IR-ADV C5045	/5051	
Canon IR-ADV C5045	/5051 PS	
Canon iR-ADV C5200	s-B2 PS V1.0	
Canon iR-ADV C5200	s-B2 PSV1.0US	
Canon iR-ADV C5235	/5240	
A 101000000		

Add: Select 'Continue'



- Select Options & Supplies

••• <> ==	Printers & Scanners	Q Search
Printers 192.168.1.240 • Idle, Default 192.168.1.248 iRADC • Idle 192.168.1.50 • Idle 192.168.1.50 • Idle Image: Straight of the straighto straighto straight of the straight of the straight of the stra		rint Queue & Supplies VV C5235/5240
	Default printer: 192.168.1 Default paper size: A4	.240 🗘 ?

- Make sure you select all of the accessories your device has.

0 • 0	< > IIII Printers & Scanners	Q Search
Printer	General Options Supply Levels Utility To take full advantage of your printer's options, confirm that they are accurately shown here. For information on your printer and its optional hardware, check the printer's documentation.	
	Cassette Feeding Unit: Off © Paper Deck Unit: Off © Output Options: None © Copy Tray: Off © Inner Finisher Additional Tray: Off © External Puncher: None © Dept. ID Managet Authentication: Mode 1 © Secured Print Authentication: Mode 1 ©	
+ -	Department ID Management Secure Printing Function of Device Cancel	ок

Step 12 - How to default your print driver Options via CUPS

If you would like to set your printer to default Single Sided or Black & White follow the below instructions on your Mac

Since CUPS uses the Internet Printing Protocol, it is also a fully-functional web server. To use your web browser to monitor the printers on your system, open Safari and type the following URL; http://localhost:631



Note:

For 10.8, the CUPS page is blocked by default. To enable it, open Terminal and type "sudo cupsctl Web Interface=yes" (without the quotation marks). Enter the admin password when prompted and then refresh the browser view. Local host can be replaced with 127.0.0.1 From the CUPS web page you can create new printers or modify existing ones

From the CUPS web page you can create new printers or modify existing ones.

Step 13 - Setting Printer Defaults via CUPS

It is possible to set the defaults of a printer driver via the CUPS admin web page. This can be helpful when a user has a colour printer but wants the default output setting to be black and white.

(Note that this does not stop a user from selecting the alternate setting. It simply sets the default so that the print dialog menus do not have to be opened.)

With the CUPS web page open, select the Printers tab and then select the printer you want to modify. Then

from the Administration drop menu, change to "Set Default Options".



This will show a new page with four menu headings (links); Options Installed, General, Banners and Policies.... Select General.

6 Home	Administration Options for ADM	Classes	Online Help 3	o Ker	Printers	A hard may
C Home Set Default ((benthme follows)	Administration Options for ADM	Cases	Coline Help 3	uba 👘	Pinters	Service and
Set Default (Options for AD	V_C7065_PS	Colline Help)	dis	Printers	C. Sand Sey
(ben him for brief i	Men.					
(ben him for brief i	Men.					
(ben him for brief i	Men.					
		nners Policies				
Options Installe	d Ceneral Ba	nners Policies				
		Ce	neral			
		Page Size	140	-		
			E Collane O No Collane			
			C brink Mining (B)			
			C Official C True			
			e efaise o True			
			K tona tauntuke iki			
			t: @#alse () True			
		Paper Output	L Laser Leftinged			
		Hole Punch				
			C (False 18)			
			L Frie B			
		OutputPartition	C (after (B)			
		C fold Setting	(female) illi			
		Face Up,Face Down	E Pinter Belact			
	Use Secure Waterm	ark Function of Device	C enfaite () True			
		Come for Numberian				

Step 14 - Setting Printer Defaults via CUPS

Scroll down the list until you find the option you want to set as default. For example, if you wanted to set the driver to a default of black & white, scroll to Colour Mode.

Print on:	Off 🗘
Paper Source:	Drawer 1
Quality.	Black and White
Color Mode 🗸	
Color Mode:	Color
Pure Black Text:	Printer Default

Note: that the Color Mode appears twice for the Canon PS driver. Both menus need to be set to Black and White for correct operation.

With the option select you then need to scroll down the list to the bottom of the page where you will see the 'Set Default Options' button.

Click this button and you will then be presented with an authentication window.

Processing Method:	Do Not Use Overlay Printing	•
Apply to:	All Pages	

Enter the account name and password that has been set as the admin for this Mac. And then press the Log In button. You will then see another page stating that the information change has been set successfully.

ė	To view this page, you must log in to area "CUPS" on 127.0.0.1:631. Your password will be sent unencrypted.
	Name: Password:
	Remember this password in my keychain Cancel Log In

You can now check that the change has been successful by selecting to print this page from Safari. With the correct printer selected change to the relevant menu, in this case Quality, to ensure your modification has worked. As shown below, the Black and White setting is now the default.

	Quality	
	Quality:	
		Quality Settings
	Color Mode:	
	Black and White	
		Profile Settings
2		Profile Settings
Device Preview		Profile Settings
Device Preview Printer Info		Profile Settings

Complete!

Please contact us if you have any further questions (Don't forget to quote your BMS ID number, found on the sticker on the front of your machine.)



Helping our customers better utilize technology & build value in their businesses.

w: thebmsgroup.com.au e: info@thebmsgroup.com.au p: 02 4254 5444