

## COMPRESSOR DATA SHEET

### Rotary Compressor: Fixed Speed

| MODEL DATA - FOR COMPRESSED AIR |                                                                                              |              |                         |
|---------------------------------|----------------------------------------------------------------------------------------------|--------------|-------------------------|
| 1                               | Manufacturer: <b>Mattei Compressors Inc.</b>                                                 |              |                         |
| 2                               | Model Number: <b>AC 30 LX</b>                                                                |              | Date: <b>Nov-16</b>     |
|                                 | <input checked="" type="checkbox"/> Air-cooled <input type="checkbox"/> Water-cooled         | Type:        | <b>Vane</b>             |
|                                 | <input checked="" type="checkbox"/> Oil-injected <input type="checkbox"/> Oil-free           | # of Stages: | <b>1</b>                |
| 3*                              | Rated Capacity at Full Load Operating Pressure <sup>a, e</sup>                               | <b>201.3</b> | acfm <sup>a, e</sup>    |
| 4                               | Full Load Operating Pressure <sup>b</sup>                                                    | <b>102</b>   | psig <sup>b</sup>       |
| 5                               | Maximum Full Flow Operating Pressure <sup>c</sup>                                            | <b>116</b>   | psig <sup>c</sup>       |
| 6                               | Drive Motor Nominal Rating                                                                   | <b>40</b>    | hp                      |
| 7                               | Drive Motor Nominal Efficiency                                                               | <b>94.1</b>  | percent                 |
| 8                               | Fan Motor Nominal Rating (if applicable)                                                     | <b>n/a</b>   | hp                      |
| 9                               | Fan Motor Nominal Efficiency                                                                 | <b>n/a</b>   | percent                 |
| 10*                             | Total Package Input Power at Zero Flow <sup>e</sup>                                          | <b>11.02</b> | kW <sup>e</sup>         |
| 11                              | Total Package Input Power at Rated Capacity and Full Load Operating Pressure <sup>d</sup>    | <b>39.78</b> | kW <sup>d</sup>         |
| 12*                             | Specific Package Input Power at Rated Capacity and Full Load Operating Pressure <sup>e</sup> | <b>19.76</b> | kW/100 cfm <sup>e</sup> |

\*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator. Consult CAGI website for a list of participants in the third party verification program: [www.cagi.org](http://www.cagi.org)

NOTES:

- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.
- c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.
- d. Total package input power at other than reported operating points will vary with control strategy.
- e. Tolerance is specified in ISO 1217, Annex C, as shown in table below:



| Volume Flow Rate<br>at specified conditions |                       | Volume Flow Rate | Specific Energy<br>Consumption | No Load / Zero Flow<br>Power |
|---------------------------------------------|-----------------------|------------------|--------------------------------|------------------------------|
| m <sup>3</sup> / min                        | ft <sup>3</sup> / min | %                | %                              |                              |
| Below 0.5                                   | Below 15              | +/- 7            | +/- 8                          | +/- 10%                      |
| 0.5 to 1.5                                  | 15 to 50              | +/- 6            | +/- 7                          |                              |
| 1.5 to 15                                   | 50 to 500             | +/- 5            | +/- 6                          |                              |
| Above 15                                    | Above 500             | +/- 4            | +/- 5                          |                              |

ROT 030

10/11 R8

This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data.