MODEL DATA - FOR COMPRESSED AIR							
1	Manufacturer: Mattei Compressors Inc						
	Model Number: AC 45 LX	Date:	Nov-16				
2	X Air-cooled Water-cooled	Type:	Vane				
	X Oil-injected Oil-free	# of Stages:	1				
3*	Rated Capacity at Full Load Operating Pressure <sup>a, e</sup>	301.0	acfm <sup>a,e</sup>				
4	Full Load Operating Pressure <sup>b</sup>	102	psig <sup>b</sup>				
5	Maximum Full Flow Operating Pressure <sup>c</sup>	116	psig <sup>c</sup>				
6	Drive Motor Nominal Rating	60	hp				
7	Drive Motor Nominal Efficiency	95.0	percent				
8	Fan Motor Nominal Rating (if applicable)	1.5	hp				
9	Fan Motor Nominal Efficiency	86.0	percent				
10*	Total Package Input Power at Zero Flow <sup>e</sup>	15.10	kW <sup>e</sup>				
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure <sup>d</sup>	59.80	$\mathbf{k}\mathbf{W}^{\mathrm{d}}$				
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure <sup>e</sup>	19.87	kW/100 cfm <sup>e</sup>				

ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.

b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.

c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.d. Total package input power at other than reported operating points will vary with control strategy.e. Tolerance is specified in ISO 1217, Annex C, as shown in table below:

Member

	Volu	Volume Flow Rate		Specific Energy	No Load / Zero Flow
	at spec	ified conditions	Volume Flow Rate	Consumption	Power
	$m^3/min$	<u>ft3 / min</u>	%	%	
	Below 0.5	Below 15	+/- 7	+/- 8	
	0.5 to 1.5	15 to 50	+/- 6	+/- 7	+/- 10%
	1.5 to 15	50 to 500	+/- 5	+/- 6	
ROT 030	Above 15	Above 500	+/- 4	+/- 5	