## **COMPRESSOR DATA SHEET**

Rotary Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR							
1	Manufacturer: Mattei Compressors I	Inc.					
2	Model Number: <b>OPTIMA 75</b>	Date:	Apr-15				
	x Air-cooled Water-cooled	Type:	Vane				
	X Oil-injected Oil-free	# of Stages:	1				
3	Rated Operating Pressure	116	psig <sup>b</sup>				
4	Drive Motor Nominal Rating	100	hp				
5	Drive Motor Nominal Efficiency	95.4	percent				
6	Fan Motor Nominal Rating (if applicable)	3.2	hp				
7	Fan Motor Nominal Efficiency	n/a	percent				
	Input Power (kW)	Capacity (acfm) <sup>a,d</sup>	Specific Power (kW/100 acfm) <sup>d</sup>				
	91.32 Max	455.2	20.06				
0*	84.54	429.6	19.68				
8*	71.57	378.2	18.92				
	59.32	326.6	18.16				
	47.77	274.8	17.39				
	42.25 Min	248.8	16.98				
9*	Total Package Input Power at Zero Flow <sup>c, d</sup>	7.91	kW				
10	35.00  30.00  25.00  15.00  20.00  15.00  10.00  25 50 75 100 125 150 175 200 225 250 275 300 325 350 375 400 425 450 475 500  Capacity (ACFM)  Note: Graph is only a visual representation of the data in Section 8  Note: Y-Axis Scale, 10 to 35, + 5kW/100acfm increments if necessary above 35  X-Axis Scale, to to 25% over maximum capacity						

\*For models that are tested in the CAGI Performance Verification Program, these items are verified by program administrator

Consult CAGI website for a list of participants in the third party verification program: <a href="www.e">www.e</a>
NOTES:</a>
<a href="www.e">a</a>. Measured at the discharge terminal point of the compressor package in accordance with</a>

www.cagi.org

- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; acfm is actual cubic feet per minute at inlet conditions.

  b. The operating pressure at which the Capacity and Electrical Consumption were measured for this data sheet.

  c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
$\underline{\mathbf{m}^3 / \mathbf{min}}$	<u>ft3 / min</u>	%	%	
Below 0.5	Below 15	+/- 7	+/- 8	
0.5 to 1.5	15 to 50	+/- 6	+/- 7	+/- 10%
1.5 to 15	50 to 500	+/- 5	+/- 6	
Above 15	Above 500	+/- 4	+/- 5	

ROT 031

This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data.