COMPRESSOR DATA SHEET

Rotary Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR							
1	Manufacturer: Mattei Compressors	Inc.					
2	Model Number: OPTIMA 90	Date:	Jan-17				
	x Air-cooled Water-cooled	Type:	Vane				
	X Oil-injected Oil-free	# of Stages:					
3	Rated Operating Pressure	116	psig ^b				
4	Drive Motor Nominal Rating	120	hp				
5	Drive Motor Nominal Efficiency	95.4	percent				
6	Fan Motor Nominal Rating (if applicable)	3.2	hp				
7	Fan Motor Nominal Efficiency	n/a	percent				
	Input Power (kW)	Capacity (acfm) ^{a,d}	Specific Power (kW/100 acfm) ^d				
	108.6 Ma	548.4	19.80				
Out	101.1	519.1	19.47				
8*	86.6	459.1	18.86				
	72.7	395.9	18.36				
	59.3	330.2	17.97				
	52.9 Mi	n 296.6	17.82				
9*	Total Package Input Power at Zero Flow ^{c, d}	9.9	kW				
10	35.00						
	25.00 (KW/100 A CFM) 20.00 20.00						
	15.00						
	10.00 0 50 100 150 200 25	0 300 350 400 450	500 550 600				
	Сар	acity (ACFM)					
	Note: Y-Axis Scale, 10 to 35, + 5k	Note: Graph is only a visual representation of the data in Section 8 Note: Y-Axis Scale, 10 to 35, + 5kW/100acfm increments if necessary above 35 X-Axis Scale, 0 to 25% over maximum capacity					

*For models that are tested in the CAGI Performance Verification Program, these items are verified by program administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org

a. Measured at the discharge terminal point of the compressor package in accordance with

Member

NOTES:

ISO 1217, Annex E; acfm is actual cubic feet per minute at inlet conditions.

- b. The operating pressure at which the Capacity and Electrical Consumption were measured for this data sheet. c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%,
- manufacturer may state "not significant" or "0" on the test report. d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:
- NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m³/min	ft3 / min	%	%	
Below 0.5	Below 15	+/- 7	+/- 8	
0.5 to 1.5	15 to 50	+/- 6	+/- 7	+/- 10%
1.5 to 15	50 to 500	+/- 5	+/- 6	
Above 15	Above 500	+/- 4	+/- 5	

ROT 031

This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data.