<u>Tuff-Spun</u> **Foot-Lover** #410/#411/#414/#430/#431/#432

DRY AREA ANTI-FATIGUE



T

Tuff-Spun Foot-Lover closed cell PVC sponge optimizes economical comfort and fatigue relief! Relieves stress on knee, foot and ankle joint pressure points. Offers a safe non-slip surface that reduces the risk of falls. Provides better slip resistance and improved insulation than that of ceramic and cement floors.

APPLICATIONS

Provide a light duty solution for dry areas - service counters, mail rooms, cashier stations, and warehouse packaging stations.

FEATURES

- Available in three slip-resistant surfaces: pebble, ribbed and diamond
- Economical anti-fatigue mat
- Beveled edges help reduce tripping

MAT SIZES:

2'x3' 3'x5' 3'x12' 27" x 36" Size is only available in Tuff-Spun Foot Lover ribbed,

in colors Black or Gray

ROLL SIZES: 2'x 60' 3'x 60' 4'x 60' 6'x 60'

WARRANTY: Total Confidence



PVC FoamABRASION RESISTANCE \leq 1.0 gram loss per ASTM D4060RESILICENCY \geq 8% per ASTM D2632ELECTRICAL PROPERTIESPR10 ¹¹ ohms (Ω) per ASTM D2570STRENGTH4 lbs per ASTM D624 die-TFLAMMABILITYD.O.CFF-1-70	MATERIAL
≤ 1.0 gram loss per ASTM D4060 RESILICENCY ≥ 8% per ASTM D2632 ELECTRICAL PROPERTIES PR10 ¹¹ ohms (Ω) per ASTM D2570 STRENGTH 4 lbs per ASTM D624 die-T FLAMMABILITY	PVC Foam
RESILICENCY≥ 8% per ASTM D2632ELECTRICAL PROPERTIESPR10 ¹¹ ohms (Ω) per ASTM D2570STRENGTH4 lbs per ASTM D624 die-TFLAMMABILITY	ABRASION RESISTANCE
≥ 8% per ASTM D2632 ELECTRICAL PROPERTIES PR10 ¹¹ ohms (Ω) per ASTM D2570 STRENGTH 4 lbs per ASTM D624 die-T FLAMMABILITY	≤ 1.0 gram loss per ASTM D4060
ELECTRICAL PROPERTIES PR10 ¹¹ ohms (Ω) per ASTM D257O STRENGTH 4 lbs per ASTM D624 die-T FLAMMABILITY	RESILICENCY
PR10 ¹¹ ohms (Ω) per ASTM D257O STRENGTH 4 lbs per ASTM D624 die-T FLAMMABILITY	≥ 8% per ASTM D2632
STRENGTH 4 lbs per ASTM D624 die-T FLAMMABILITY	ELECTRICAL PROPERTIES
4 lbs per ASTM D624 die-T FLAMMABILITY	PR10 ¹¹ ohms (Ω) per ASTM D257O
FLAMMABILITY	STRENGTH
	4 lbs per ASTM D624 die-T
D.O.CFF-1-70	FLAMMABILITY
	D.O.CFF-1-70

#410/#411/#414 - 3/8"Thickness #430/#431/#432 - 5/8"Thickness



Working Hard for the Hard Working[®]

WE OFFER A 48 HOUR SHIPPING GUARANTEE FOR IN-STOCK ORDERS.