

Corrugated Switchboard Runner V-groove non-conductive surface insulates worker to prevent shock!


- Every roll is proof tested at the specified voltage, over the entire surface of the matting to ensure best protection
- Ideal for industrial environment
- As a non-conductive mat, Corrugated Switchboard Runner brings safety and security to a higher degree

CORRUGATED SWITCHBOARD APPLICATIONS

Provides a heavy duty solution for dry areas e.g.: Computer workstation, Fuse box, Control panel and Switchboard.

FEATURES

- Dielectric rating: 30,000 volts
- Meets ASTM standards: D178, Type 2, Class 2
- Meets all optional ASTM standards for resistance to ozone, flames and oils



BLACK

AVAILABILITY		TECHNICAL DATA	PROFILE
STANDARD SIZES	ROLLS	Weight: .64lbs per sq. ft. Material: Extruded vinyl Surface: Corrugated Tensile strength: 700 PSI meets ASTM-D-412 Flammability: Meets ASTM-D-1962 Oil resistance: Meets ASTM-D-471	 Thickness: 1/4"
Unavailable	3' X 75'		
CUSTOM SIZES			
Length cuts up to 75'			
USE AND CARE		WARRANTY	
Vacuum		Standard limited one year	

AUTHORIZED DISTRIBUTOR