

Hydrosense Ultra Legionella Industrial Kit Data Sheet

This kit is designed to test for *Legionella* in risk areas identified by CDC* such as:

- Pipe fittings in domestic and industrial hot and cold water systems.
- Cooling towers.
- Showers.
- Water tanks.



*The Centers for Disease Control and Prevention (CDC) is a federal agency that conducts and supports health promotion, prevention and preparedness activities in the United States, with the aim of improving overall public health.

Hydrosense Ultra *Legionella* Industrial Kit product code 100182

The test kit contains all the items required to perform 5 tests and includes a fitting for connection to water systems.

- The test detects Legionella pneumophila serogroup 1 (LpSG1).
- With filtration step, the sensitivity of the water test is 100
- The test detects Viable-But-Non-Culturable Bacteria and Legionella SG1 in all stages of its life-cycle.
- Hassle free sample collection. Simply connect sample point to the water system and use system pressure to drive the filtration process.
- The kit includes single-use filtration modules.

- The kit includes pre-filled syringes containing recovery buffer. No need to measure or dilute solutions.
- The test is simple to use and helps to minimise delays and downtime
- The test provides straightforward results, on-site, within 25–35 minutes.
- Regular use increases confidence in Legionella controls.
- The smartphone App reader provides independent record of results (Download Hydrosense App for free from the App store or Play Store).

Hydrosense uses Lateral Flow Immunochromatographic Assay (LFICA) technology to detect the presence of cell surface antigens from *Legionella* bacteria. It uses *Legionella* antibodies, tagged with red nanoparticles, which bind to any bacteria found in the sample and make them visible on a line on the device. The test works just like a pregnancy test - one line indicates a negative result and two lines indicate a positive result.



hydrosense

Bacteria detected	Legionella pneumophila serogroup 1		
Detection method	Lateral flow immunochromatographic assay		
Limit of detection	100 CFU/L (0.1 CFU/mL)		
Specificity	Tested against a wide range of waterborne bacteria, including Acinetobacter calcoaceticus, Aeromonas hydrophila subsp. hydrophila, Bacillus subtilis, Burkholderia cepacia, Citrobacter freundii, Citrobacter koseri, Escherichia coli, Enterobacter cloacae, Klebsiella oxytoca, Pseudomonas aeruginosa, Pseudomonas fluorescens, Pseudomonas putida, Pseudomonas stutzeri, Ralstonia pickettii, Raoultella terrigena, Streptococcus pyogenes, Yersinia ruckeri.		
	Organism	≥cfu/mL	
	L.p Sg-2,3,8,11,13,14	1.00E+08	
	L.p. Sg-4,5,6,7,9,10,15	1.00E+07	
	L.p. Sg-12	8.00E+06	
	S.aureus	2.00E+08	
	The Hydrosense <i>Legionella pneumophila</i> SG1 test has been shown to produce weak positive results with other <i>Legionella pneumophila</i> serogroups at the cfu/mL stated in the above table.		
Test volume	100 μL		
Suggested sample volume	250 mL		
Sample parameters	pH range Sample temperature range Environmental operating range 1 Free chlorine concentration Total Alkalinity Total Hardness Sample should filter in less than 10 minute	5–10 15–45 °C (59–113 °F) 5–40 °C (59–104 °F) <5ppm <1000 ppm <1000 ppm	
used in <i>Legionella</i> control, at their norm		of common biocides and biodispersants maximum operating concentration. Active , didecyl-dimethyl-ammonium chloride, ionic and non-ionic surfactants.	
	The test gives a false positive if used with systems treated with polymeric biguanide or THPS. It should not be used to test such systems.		
Operator time	5–10 minutes		
Test time	25 minutes		
Sample point fitting	Supplied with both $\frac{1}{2}$ " and $\frac{3}{4}$ " female threaded fittings. Additional sample points are available (part no. 100171).		
Shelf life		18 months from date of manufacture, when stored at room temperature (<30°C) in original packaging. All test strips are hermetically foil-wrapped and with a printed expiry date.	

