

# Connect to North America

Plugs and receptacles by rating



U.S.A.  
P.O. Box 115, Oskaloosa, IA 52577  
United States/Canada, Puerto Rico, Virgin Islands  
Toll-Free Phone: (800) 662-2290 • Toll-Free Fax: (800) 645-5360  
International  
Phone: (641) 673-5000 • Fax: (641) 673-5100

UK  
10 Kelvin Drive • Knowlhill, Milton Keynes  
Buckinghamshire MK5 8NH  
UK, Ireland, Germany, Switzerland, Austria  
FreePhone: 00800 5566 5566 • Freefax: 00800 5655 5655  
International  
Phone: +44 (0)1908 295300 • Fax: +44 (0)1908 295301

Rev. 10-17



Rating	NEMA Configuration	Style	Plug	In-Line Connector	Receptacle Single	Receptacle Duplex	Flanged Inlet	Flanged Outlet	Recommended Cable	
15A 125VAC		5-15	Straight blade	88030100	88030110	88031010	88030070	88031040	88031030	<b>For 15A Devices:</b> PVC: <b>86060130</b> 3 x 14AWG, SJT, 18A/300VAC Approx. O.D.: 9.4mm Wiring Code: black, white, green 
		5-15	Straight blade, Hospital-Grade	88030270	88030280	88030290	88030890	—	—	
		L5-15	Locking	88030240	88030250	—	88031220	88030480	88030490	
15A 250VAC		6-15	Straight blade	88030200	88030210	88030610	88030590	88030440	88030450	<b>TPE: 86030530</b> 3 x 14AWG, SJEOW/SJTOW, 18A/300VAC Approx. O.D.: 9.4mm Wiring Code: black, white, green 
		6-15	Straight blade, Hospital-Grade	88030370	—	—	88030830	—	—	
		L6-15	Locking	88030220	88030230	—	88030640	88030650	88030660	
20A 125VAC		5-20	Straight blade	88030120	88030130	88030080	88030430	88030460	88030330	<b>For 20A Devices:</b> PVC: <b>86060140</b> 3 x 12AWG, SJT, 25A/300VAC Approx. O.D.: 11.1mm Wiring Code: black, white, green 
		5-20	Straight blade, Hospital-Grade	88030390	88030400	88030580	88030940	—	—	
		L5-20	Locking	88030140	88030150	88030300	—	88030500	88030510	
20A 250VAC		6-20	Straight blade	88030180	88030190	88030620	88030600	88030470	88030030	<b>TPE: 86030500</b> 3 x 12AWG, SEOW/STOW, 25A/600VAC Approx. O.D.: 16.1mm Wiring Code: black, white, green 
		6-20	Straight blade, Hospital-Grade	88030410	—	—	—	—	—	
		L6-20	Locking	88030160	88030170	88031081	—	88030090	88030530	
30A 125VAC		L5-30	Locking	88031070	88031160	—	—	—	—	<b>For 30A Devices:</b> PVC: <b>86030430</b> 3 x 10AWG, SJT, 30A/300VAC Approx. O.D.: 15.0mm Wiring Code: black, white, green TPE: none 
30A 250VAC		L6-30	Locking	88030310	88030320	—	—	88030040		