Technical Specifications

New Generation Terrazzo Tile Range (Page 1 of 2)

Resistance to Salt Attack AS/NZS 4456.10B	Protected		General Purpose			Exposure	
						\	
	Only suitable for use in locations protected from external weathering		Resistant to decay in non-saline environments (e.g. normal external paving)			Resistant to decay in saline environments (e.g. pool surrounds)	
Dimensional Deviation AS/NZS 4456.3B	DP0	DPB1	DPB2	DPB3	DPB4		
					/		
	No Requirement	Plan: +/- 3.0 Std Deviation: 2.0 Height: +/- 2.5 Std Deviation: 3.0	Plan: +/- 2.5 Std Deviation: 2.0 Height: +/- 2.0 Std Deviation: 3.0	Values as agreed between supplier and purchaser.	Plan: +/- 2.0 Std Deviation: 1.5 Height: +/- 2.0 Std Deviation: 2.0		
Breaking Load of Segmental Pavers AS/NZS 4456.5		Residential	Public Space		Public Space		
	Pedestrian	Light Vehicle	Commercial	Pedestrian	Light Vehicle	Commercial	Trafficked
300 x 300 x 40mm	/			/			
400 x 400 x 40mm	/			/			
300 x 300 x 50mm	/	/		/	/		
600 x 300 x 50mm	/			/			
300 x 200 x 60mm	/	/	/	/	/	/	✓
300 x 300 x 60mm	/	/	/	/	/		✓
400 x 400 x 60mm	/	/		/	/		
600 x 400 x 60mm	/	<u> </u>		<u> </u>	/		
	A pavement only sub- jected to foot traffic	A vehicle with gross weight of less than 3 ton.	A vehicle with gross weight of more than 3 ton.	A pavement only subjected to foot traffic	A vehicle with gross weight of less than 3 ton.	A vehicle with gross weight of more than 3 ton.	Vehicles per day: Minor: <400 Local: 400-1000 Collector: 1000-2000



Technical Specifications

New Generation Terrazzo Tile Range (Page 2 of 2)



Slip Resistance AS 4586:13	Surface Finish	P0 & P1	P2	P3	P4	P5		
	Honed	/	✓	/	/			
	Black Series	/	✓	/	/	/		
	Sawn	/	✓	/	/	/		
		Internal dry areas only	Internal areas subjected to occasional water tracking	Undercover carparks Undercover concourses Dry stair treads	External walkways Wet stair treads Swimming pool surrounds	External ramps Loading docks Swimming pool ramps		
Skid Resistance as per DPTI Test Procedure TN024 01/2016 based on 5000 wear cycles	Surface Finish	Test						
	Honed							
	Black Series	/	(300x300x60mm 300x200x60mm Thickness only)					