

Technical Specifications

Traditional Paver Range (Page 1 of 2)



Breaking Load of Segmental Pavers AS/NZS 4456.5	Residential			Public Space			Trafficked
	Pedestrian	Light Vehicle	Commercial	Pedestrian	Light Vehicle	Commercial	
Patio Paver 40 (380x190x40mm)	✓			✓			
Flag 40 (190x190x40mm)	✓			✓			
Best Paver 40 (220x110x40mm)	✓			✓			
New Flag 40 (220x220x40mm)	✓			✓			
Slab 40 (300x300x40mm)	✓			✓			
Best Paver 50 (220x110x50mm)	✓	✓		✓	✓		
Flag 50 (220x220x50mm)	✓	✓		✓	✓		
Slab 50 (300x300x50mm)	✓	✓		✓	✓		
Best Paver 60 (220x110x60mm)	✓	✓	✓	✓	✓	✓	
Flag 60 (220x220x60mm)	✓	✓	✓	✓	✓	✓	
Slab 60 (300x300x60mm)	✓	✓	✓	✓	✓	✓	
Best Lock 60 (190x190x60mm)	✓	✓	✓	✓	✓	✓	✓
Esse Paver 60 (220x110x60mm)	✓	✓	✓	✓	✓	✓	✓
Best Paver 80 (220x110x80mm)	✓	✓	✓	✓	✓	✓	✓
Esse Paver 80 (220x110x80mm)	✓	✓	✓	✓	✓	✓	✓
Bio Paver 60 (220x110x60mm)	✓	✓	✓	✓	✓	✓	
Bio Lock 60 (190x190.x60mm)	✓	✓	✓	✓	✓	✓	✓
	A pavement only subjected to foot traffic	A vehicle with gross weight of less than 3 ton.	A vehicle with gross weight of more than 3 ton.	A pavement only subjected to foot traffic	A vehicle with gross weight of less than 3 ton.	A vehicle with gross weight of more than 3 ton.	Vehicles per day: Minor: <400 Local: 400-1000 Collector: 1000-2000

Technical Specifications

Traditional Paver Range (Page 2 of 2)



Resistance to Salt Attack AS/NZS 4456.10B	Protected		General Purpose			Exposure
		Only suitable for use in locations protected from external weathering		Resistant to decay in non-saline environments (e.g. normal external paving)		
Dimensional Deviation AS/NZS 4456.3B	DPB0	DPB1	DPB2	DPB3	DPB4	
	No Requirement	Plan: +/- 3.0 Std Deviation: 2.0 Height: +/- 2.5 Std Deviation: 3.0	Plan: +/- 2.5 Std Deviation: 2.0 Height: +/- 2.0 Std Deviation: 3.0	Values as agreed between supplier and purchaser.	Plan: +/- 2.0 Std Deviation: 1.5 Height: +/- 2.0 Std Deviation: 2.0	✓
Slip Resistance AS 4586:13	Surface Finish	P0 & P1	P2	P3	P4	P5
	Traditional	✓	✓	✓	✓	✓
	Honed	✓	✓	✓	✓	
	Weathered	✓	✓	✓	✓	✓
	Pebble	✓	✓	✓	✓	✓
		Internal dry areas only	Internal areas subjected to occasional water tracking	Undercover car parks Undercover concourses Dry stair treads	External walkways Wet stair treads Swimming pool surrounds	External ramps Loading docks Swimming pool ramps