

Centralfeeder

feed GIIIIIIIID

A waterborne central feeder that ensures safe feeding of cleaner fish. Avoid feed spill with continuous feeding in all pens.

Centralfeeder offers parallel feeding of cleaner fish in all pens. Feed amount and up to 4 time intervals per day are controlled from a pc.

The feeder can feed up to 10 pens simultaneously - with up to 3 distribution points per pen. Waterborne feeding at desired depth - where the fish is located - will avoid the impact of wind and surface currents.

Waterborne Feeding is considerably gentler on both the pellets and the feeding pipe, and noise and micro-plastic discharge are reduced to an absolute minimum. You will also experience a significant drop in energy consumption by replacing air with water. In addition, new feed pipes will be cheaper as you don't need to purchase antistatic pipes.

Centralfeeder is part of the feedGOOD portfolio - OK Marine's products in the cleaner fish feed segment.

31 ECII ICATIONS		
L/W/H:	1600 / 1220 / 1310 mm	
Dry weight:	800 kg	
Silo capacity:	1000 liter	
Power supply:	32a / 400v / 50 hz / 3 phase	
Dosing capacity:	10 x 0-50 kg/hour	
Pump pressure:	Max. 3.5 bar	

Max. 80 liter/min

Cloud based HMI, insulation,

flowmeters, pressure sensors

Contact us

Pump flow:

Options:

Inge Salvesen, Sales Manager inge@okmarine.no
Phone: +47 40 63 99 97

SPECIFICATIONS

In cooperation with **AKVA** GROUP

