

# Rewriting the Benchmark with Unparalleled Speed



TX-5300 Max. Print Width	TX-5400 Max. Print Width	LUCIA TD ink	FINE FINEst Engineering and Inkjet Engineering
L-COA PRO	5pl Ink droplet size	Multifunction Roll System	Line Accuracy: +/- 0.1% or less
100 Sheets High Capacity Stacker	MFP	WiFi Connectivity	Direct USB Drive Printing

## Raising the Bar in Print Speed and Quality

Meet the latest imagePROGRAF TX-5300 and TX-5400. Engineered to deliver amazing print speed with sharp reproduction of lines and text even on uncoated paper. Boost productivity with improved features such as Multifunction Roll System, MFP solution, and Wifi connectivity.

# SPECIFICATIONS

imagePROGRAF  
TX-5300 | TX-5400

PRINTER	TX-5300		TX-5400	
Printer Type	5 Colour 36"		5 Colour 44"	
Number of Nozzles	15,360 nozzles; (MBK 5,120 nozzles, BK, C, M, Y 2,560 nozzles each)			
Print Resolution	2400 dpi x 1200 dpi			
Nozzle Pitch	1200dpi (2lines)			
Line Accuracy	±0.1 % or less			
Ink Droplet Size	5 Picoliter			
Ink Capacity	160ml/330ml/700ml; Bundled Starter Ink : 330ml (MBK)/160ml (BK, C, M, Y)			
Ink Type	Pigment inks/5 color - MBK/BK/C/M/Y			
Printer Languages	SG Raster (Swift Graphic Raster), HP-GL/2, HP RTL , PDF (Ver.1.7), JPEG (Ver. JFIF 1.02)			
Standard Interfaces	USB B Port: Built in (Hi-Speed USB ), Full Speed (12 Mbit/sec), High Speed (480 Mbit/sec), Bulk transfer, Series B (4 pins); USB A Port: USB Memory Direct Print Gigabit Ethernet: IEEE 802.3 10base-T, IEEE 802.3u 100base-TX / Auto-Negotiation, IEEE 802.3ab 1000base-T/ Auto-Negotiation, IEEE 802.3x Full Duplex Wireless LAN: IEEE802.11n/ IEEE802.11g/ IEEE802.11b			
Memory	Standard memory: 128GB (Physical memory 2GB)			
Hard Disk	500GB (Encrypted)			
PRINTING SPEED (A0 SIZE)				
Plain Paper (CAD Drawings)	00:37 Fast (Custom Q5)		00:40 Fast	
Heavyweight Coated paper HG (CAD Drawings)	00:45 Fast (Custom Q5)		01:11 Fast	
Plain Paper (Poster)	00:42 Fast (Custom Q5)		00:42 Fast	
Heavyweight Coated paper HG (Poster)	01:43 Fast		02:37 Standard	
MEDIA HANDLING				
Media Width	Roll paper: 203.2 ~ 917mm, Cut sheet: 203.2 ~ 917mm		Roll paper: 203.2 ~ 1118mm, Cut sheet: 203.2 ~ 1118mm	
Media Thickness	Roll paper / Cut: 0.07 ~ 0.8mm			
Minimum Printable Length	203.2 mm			
Maximum Printable Length	Roll paper: 18 m, Cut sheet: 1.6 m			
Maximum Media Roll Outer Diameter	170 mm			
Paper Feed Method	Roll Paper: One Roll, Front-loading, Front Output; Added Roll Paper: One Roll, Front-loading, Front Output; Cut Sheet: Front-loading, Front Output (Manual feed using media locking lever)			
Media Take-up Unit	Dual directions rolling take-up			
Borderless Printing Width (Roll Only)	594mm (ISO A1), 841mm (ISO A0), 10", 14", 17", 24", 36", 42", 44"			
Media Output (Multiposition Basket)	Standard position: 1 sheet, Flat position: A2 landscape [<10 sheets glossy paper; <20 sheets coated or plain paper]			
Media Output (High Capacity Stacker)	Standard Basket: 10 sheets, Flat Position: 100 sheets (A1 Landscape), Draped Position: 100 sheets (A0 Portrait)			
DIMENSIONS & WEIGHT				
Packaged Dimensions W x D x H (mm) / Weight (kg)	Printer (with stand and pallet)	1606 x 903 x 1061 mm, Weight : 153kg		1820 x 915 x 1061 mm, Weight : 165kg
	High Capacity Stacker	1249 x 906 x 291 mm, Weight : 24kg		1464 x 906 x 291 mm, Weight : 25kg
	Roll Unit	1524 x 562 x 461 mm, Weight : 26kg		1727 x 562 x 461 mm, Weight : 30kg
Physical Dimensions W x D x H (mm) / Weight (kg) (including Roll Holder Set and Roll unit, excluding ink and print head)	Main Unit + Stand + Basket	Basket Opened: 1390 x 984 x 1168 mm		Basket Opened: 1593 x 984 x 1168 mm
		Basket Closed: 1390 x 766 x 1168 mm		Basket Closed: 1593 x 766 x 1168 mm
		105 kg (including Roll Holder Set, excluding ink and print head)		114 kg (including Roll Holder Set, excluding ink and print head)
	Main Unit + Roll Unit + Stand + High Capacity Stacker	Stacker Opened: 1390 x 1188 x 1168 mm		Stacker Opened: 1593 x 1188 x 1168 mm
		Stacker Closed: 1390 x 1122 x 1168 mm		Stacker Closed: 1593 x 1122 x 1168 mm
		136 kg (including Roll Holder Set, excluding ink and print head)		146 kg (including Roll Holder Set, excluding ink and print head)
POWER AND OPERATING REQUIREMENTS				
Power Supply	AC 100-240V (50-60Hz)			
Power Consumption	Operation: 105W or less, Sleep mode: 3.6W or less, Power off : 0.3W or less			
Operating Environment	Temperature: 15~30°C, Humidity: 10~80% RH (no dew condensation)			
Acoustic Noise	Power	Operation: 6.9 Bels or less		
	Pressure	Operation: 51dB (A) or less; Standby: 35dB (A) or less		
OPTIONS				
Roll Unit	TX-5300 RU-32		TX-5400 RU-42	
High Capacity Stacker	SS-31		SS-41	
2/3" Roll Holder	RH2-34		RH2-45	
CONSUMABLES				
Ink Tank	PFI-8110 (160ml) / PFI-8310 (330ml) / PFI-8710 (700ml)			
Print Head	PF-06			
Cutter Blade	CT-07			
Maintenance Cartridge	MC-30			
SCANNER				
Scan Width	36" (914mm)			
Min Scan width	6" (150mm)			
Max Scan length	8m (JPEG/PDF); 15.2m (TIFF)			
Scan Speed (Color/B&W)	6.0/13 ips			
Optical Resolution	1200dpi			
Max Document Thickness	2.0mm			
PC & Software Included	15.6" AIO PC with SmartWorks MFP Software			
Software Features	Scan, Copy, Print. Preview Edit. PDF, PDF/A, Multipage PDF. User Accounts, job log. Collated sets. Custom paper sizes. Adjust JPEG compression.			
Dimensions W x D x H (mm) / Weight (kg)	1109 x 367 x 161mm, Weight : 15kg			

**Canon**  
Delighting You Always

CANON SINGAPORE PTE. LTD.  
1 Fusionopolis Place, #15-10 Galaxis, Singapore 138522  
Tel : 65-6799-8888 | Fax : 65-6799-8882 | www.canon-asia.com



SCAN HERE  
FOR MORE INFO

CANON BUSINESS PARTNER / DEALER'S STAMP

This document is for information purpose only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.  
Warning: Unauthorised recording of copyrighted materials may infringe on the rights of copyright owners and may be contrary to copyright laws.