



ISL-SECFLOOD1000

Metal Security Flood Light

- Detached Solar Panel for Optimum Sun Exposure & Mounting
- 6000K Pure White
- Lamp Brightness: 1100lm
- 180°/26' Motion Detection Range
- 196' Lighting Range
- Approximate Lighting Times:
 - Constant Dim Lighting: 11 Hour Run Time Approx
 - Bright Light: 200 Times @ 30 Seconds Each in Dim Lighting
- 6-8 Hour Charge Time
- Rugged Materials:
 - Stainless Steel, Toughened Glass & Aluminum Plate

Model	ISL-SECFLOOD1000
Solar Panel	tempered glass laminate 6V*6W
Battery	18650 lithium 3.7V/5200mA
Protection voltage	2.5V
Working voltage	3.7 V
Maximum Voltage	4.2V
Minimum Voltage	2.5V
Rated Power	20 W
Output current	6A
Maximum output power	20W
LED Specifications	COB 20W LED
LED color temperature	6000K pure white
Number of LEDs	COB 20W LED
Light flux	200-1000lm
Lighting Area Range	196'
Detection Range	>180°, 26'
Working mode	dim light when no induction ; High Light when people come
Induction mode	PIR motion Sensor
Case material	Stainless Steel
Lamp cover material	Toughened glass
Light board material	Aluminum plate
Charging time	>6-8 hrs
Working time	dim light >11hrs motion bright light 200times*30 seconds
Run Time	Turn off when no power any more , no auto off time limited.
Ingress proof rating	IP65
Product lifespan	5 years
Product Warranty	1 year(including battery)
Product Size	13.3 x 9.05 x 4.13inches (340 x 230 x105mm)
Product weight	4.18lbs (1.9KG) including packaging
Product Certification	CE ROHS

Ordering Information

ISL-SECFLOOD1000: Solar Flood Light