



ELEV-ALLMIP

2 Megapixel TVI/AHD/CVI/CVBS Pinhole Camera, 2.8/3.7mm Optional, D-WDR, Up to -40°C, 12VDC

Features

- 1080P, 1/2.9" Sony CMOS Sensor
- AHD / TVI / CVI / CVBS Output Selectable from UTC Control
- 2.8mm/3.7mm Pinhole Lens Available
- Up The Cable (UTC) function
- D-WDR
- Withstand up to -40°C operation
- 12VDC Only Operation
- Through Invid Tech DVR: Free App, CMS & Mac Client

Invid Model	ELEV-ALLMIP28/ELEV-ALLMIP37
Image Sensor	1/2.9" Sony CMOS Sensor
Signal System	NTSC/PAL
Effective Pixels	1920(H) x 1080(V)
Min. Illumination	0.01Lux
Video Frame Rate	PAL/NTSC: 1080P@ 25/30fps
Video Output	AHD / TVI / CVI / CVBS (960H)
Video Output Default	TVI
Camera Features	
S/N Ratio	>41dB
Noise Reduction	2D & 3D DNR
Day&Night	Color / B&W/ AUTO / EXT
White Balance	Auto / Manual
OSD	English / Chinese / German / French / Italian / Spanish / Polish / Russian / Portuguese / Dutch / Turkish / Korean / Japanese / Hebrew / Arabic
AGC	Auto
Mirror Image	Yes
Auto Iris	No
Sharpness	Yes
Defogging	No
BLC	Yes
D-WDR	Yes
Smart IR	No
Lens	
Lens	2.8mm pinhole, 3.7mm pinhole
View Angle	"ELEV-ALLMIP28: 89.8 Degree ELEV-ALLMIP37: 77.8 Degree"
Lens Type	Fixed Iris
Mount Type	M12
General	
Housing Material	Metal
Power Supply	DC12V(+/-10%)
Power Consumption	5W
Working Temperature / Humidity	-40°F ~ 140°F(-40~+60°C)
Dimensions(WxDxH)	25*25mm
Weight	0.22lbs(100g)

Ordering Information

ELEV-ALLMIP28: 2 Megapixel Metal Case Camera, 2.8mm
ELEV-ALLMIP37: 2 Megapixel Metal Case Camera, 3.7mm