



ELEV-C5TXIR

5-2 Megapixel Field Selectable TVI/AHD/CVI/CVBS,
Outdoor Turret, 65' IR Range, D-WDR, up to -40, 12VDC

Features

- 5-2 Megapixel Field Selectable**
- All-in-One Technology (TVI/AHD/CVI/Analog 960h)
- Fixed Lens
- True Day/Night
- D-WDR
- 65' Smart IR Range
- Up The Cable (UTC) Function
- IP66 Weather Resistant
- Withstand up to -40° Operation
- 12VDC Only Operation
- Through InVid Tech DVR:
Free App, CMS & MAC Client

| | |
|--------------------------------|---|
| Model | ELEV-C5TXIR |
| Image Sensor | 1/2.5" CMOS Sensor |
| Signal System | NTSC/PAL |
| Effective Pixels | 2592(H) x 1944(V) |
| Field of View | Horizontal: 102° Vertical:74° |
| Electronic Shutter | AUTO/ 1/50 1/60 -1/50,000sec |
| Min. Illumination | 0.01Lux |
| Video Output | "TVI:5MP 20/12.5 FPS, 4MP 30/25/12.5 FPS, 2MP 30/25 FPS AHD:5MP 20/12.5 FPS, 4 MP 30/25 FPS, 2MP 30/25 FPS CVI:4MP 30/25 FPS, 2 MP 30/25 FPS CVBS" |
| Video Output By Default | "TVI: 5MP @ 20 FPS AHD:2MP @ 30 FPS CVI: 2MP @ 30 FPS CVBS" |
| Dip Switch | Support |
| UTC Control | Support |
| Camera Features | |
| Mirror Image | Yes |
| Auto Iris | No |
| Sharpness | Yes |
| Defogging | No |
| BLC | Yes |
| D-WDR | Yes |
| S/N Ratio | >41dB |
| Noise Reduction | 2DNR |
| Day&Night | Color / B&W/ AUTO / EXT |
| White Balance | Manual/Auto |
| AGC | Auto |
| IR LED | 18pcs SMD IR |
| IR Range | Up to 65 ft |
| Lens | |
| Focal Length | 2.8mm Fixed Lens |
| Lens Type | Fixed Iris |
| Mount Type | M12 |
| General | |
| IP Rating | IP66 |
| Casing | Metal |
| Power Supply | DC12V(+/-10%) |
| Power Consumption | IR OFF:85mA / IR ON:320mA |
| Working Temperature / Humidity | -40°F-140°F(-40~+60°C) |
| Dimensions(WxDxH) | 4.00" x 3.52" |
| Weight | .82 lbs (370g) |

Ordering Information

ELEV-C5TXIR28: 5-2 Megapixel Turret, 2.8mm

**Scale down to other resolutions via camera dip switches & OSD

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.