



ELEVI-P5BXIRA2812

5 Megapixel IP Plug & Play, Outdoor Bullet, 2.8-12mm Auto-Focus Motorized, 115' IR Range, WDR, PoE/DC 12V

Features

- 5 Megapixel (2592x1944)
- Motorized Auto-Focus 2.8-12mm Lens
- H.265/H.264
- True Day/Night
- True WDR 120dB
- Smart IR Range up to 115'
- IP66 Weather Resistant
- 12VDC/PoE Operation
- Smart Analytics
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS)
- Free MAC client

Model	ELEVI-P5BXIRA2812
Sensor+DSP	IMX335+Hi3516EV300
Sensor	1/2.8" Progressive scan CMOS Sensor
Min. Illumination	0.01lux(Color), 0lux(IR on)
Lens	2.7-13.5 mm@F1.3: horizontal FOV: 108.78°~28.76°, vertical FOV:57.22°~16.2°
Lens Mount	c14
IR	14milX30pcs SMD LED
IR Range	115ft (35m)
Smart IR	Support
Shutter Time	Auto/Manual, 1/3~1/10000s
Day/Night	IR cut filter with auto switch
Wide Dynamic Range	WDR&DWDR (13fps)
Digital noise reduction	2D/3D DNR
Compression Standard	
Video Compression	H.264/H.265
H.264 Codec profile	Base/Main/High profile
H.265 Codec profile	Main profile
Video Bit Rate	11 Kbps~10 Mbps
Triple Streams	N/A
Image	
Max. Image Resolution	5MP(2592 × 1944)(default 15fps)
Frame Rate	"50Hz:15fps 5MP(2592 × 1944) 15fps 4MP(2560 × 1440),15fps 4MP(2304 × 1728) 25fps 3MP(2048 × 1536),25fps 1080P(1920 × 1080) 25fps 960P(1280 × 960), 60Hz:15fps 5MP(2592 × 1944) 15fps 4MP(2560 × 1440),15fps 4MP(2304 × 1728) 30fps 3MP(2048 × 1536),30fps 1080P(1920 × 1080) 30fps 960P(1280 × 960),30fps 720P(1280 × 720)"
Sub Stream	"50Hz:25fps 720P(1280 × 720) 25fps D1(704 × 576),25fps CIF(352 × 288) 60Hz:30fps 720P(1280 × 720) 30fps D1(704 × 480),30fps CIF(352 × 240)"
Third Stream	N/A
Image Setting	Brightness/Contrast/Saturation/Hue/Sharpness
BLC	Support
HLC	Support
ROI	Support
Defog	Support
Network	
Network Storage	N/A
Protocols	"TCP/IP,ICMP,HTTP,HTTPS,DHCP,DNS,DDNS,RTP,RTSP, RTCP,NTP,IGMP,UPnP,SMTP,UPnP-TM,P2P,Bonjour,IPv6"
Event	Motion Detection, Video Shelter
Smart Functions	Line Crossing,Area Intrusion,Region Entrance,Region Exiting,- Fast Moving,Face Detection
System compatibility	CGI
Security	User authentication,IP address filtering,Video mask
Mobile Surveillance	iPhone, iPad,Android , CMS,WEB
Interface	
Communication interface	1 RJ45 10M / 100M Ethernet Port
General	
Operating Conditions	-22°F ~ 140°F (-30°C ~ 60°C) Humidity 95% or less (non-condensing) "
Power Supply	DC12V ± 10%
POE Supply	PoE (802.3af)
Power Consumption	MAX. 8.5W
Weather Proof	IP66
Dimensions	2.63 X 8.29 Inches (67 X 210.8mm)
Weight	1.59lb (720g)

Ordering Information

ELEVI-P5BXIRA2812: 2.8-12mm A/F Motorized

Made in Indonesia

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.