



Model	ELEVI-P5TXIR
Sensor+DSP	IMX335+HI3516EV300
Sensor	1/2.8" Progressive scan CMOS Sensor
Min. Illumination	0.01lux(Color), 0lux(IR on)
Lens	2.8 mm@F1.85: horizontal FOV: 99°, vertical FOV:56°
Lens Mount	M12
IR	14milX18pcs SMD LED
IR Range	98ft (30m)
Smart IR	Support
Shutter Time	Auto/Manual, 1/3~1/10000s
Day/Night	IR cut filter with auto switch
Wide Dynamic Range	WDR&DWDR (13fps)
Digital noise reduction	2D/3D DNR
Compression Standard	
Video Compression	H.264/H.265
H.264 Codec profile	Base/Main/High profile
H.265 Codec profile	Main profile
Video Bit Rate	11 Kbps~10 Mbps
Triple Streams	N/A
Image	
Max. Image Resolution	5MP(2592 × 1944)(default 15fps) "50Hz:15fps 5MP(2592 × 1944) 15fps 4MP(2560 × 1440),15fps 4MP(2304 × 1728) 25fps 3MP(2048 × 1536),25fps 1080P(1920 × 1080) 25fps 960P(1280 × 960), 60Hz:15fps 5MP(2592 × 1944) 15fps 4MP(2560 × 1440),15fps 4MP(2304 × 1728) 30fps 3MP(2048 × 1536),30fps 1080P(1920 × 1080) 30fps 960P(1280 × 960),30fps 720P(1280 × 720)"
Frame Rate	
Sub Stream	"50Hz:25fps 720P(1280 × 720) 25fps D1(704 × 576),25fps CIF(352 × 288) 60Hz:30fps 720P(1280 × 720) 30fps D1(704 × 480),30fps CIF(352 × 240)"
Third Stream	N/A
Image Setting	Brightness/Contrast/Saturation/Hue/Sharpness
BLC	Support
HLC	Support
ROI	Support
Defog	Support
Network	
Network Storage	N/A
Protocols	"TCP/IP,ICMP,HTTP,HTTPS,DHCP,DNS,DDNS,RTP,RTSP, RTCP,NTP,IGMP,UPnP,SMTP,UPnP-TM,P2P,Bonjour,IPV6"
Event	Motion Detection, Video Shelter
Smart Functions	Line Crossing,Area Intrusion,Region Entrance,Region Exiting,-Fast Moving,Face Detection
System compatibility	Onvif(Profile S), CGI
Security	User authentication,IP address filtering,Video mask
Mobile Surveillance	iPhone, iPad,Android , CMS, WEB
Interface	
Communication interface	1 RJ45 10M / 100M Ethernet Port
General	
Operating Conditions	-22°F ~ 140°F ( -30°C ~ 60°C) Humidity 95% or less (non-condensing) "
Power Supply	DC12V ± 10%
POE Supply	PoE (802.3af)
Power Consumption	MAX. 8.5W
Weather Proof	IP66
Dimensions	3.62 x 3.46 Inches (92 x 88 mm)
Weight	0.73lb (330g)

## ELEVI-P5TXIR

5 Megapixel IP Plug & Play, Outdoor Turret, 98' IR Range, WDR, PoE/DC12V

### Features

- 5 Megapixel (2592x1944)
- Fixed Lens
- H.265/H.264 Compression
- True Day/Night
- True WDR 120dB
- Smart IR Range up to 98'
- TF Card Local Storage, 128GB
- IP66 Weather Resistant
- 12VDC/PoE Operation
- ONVIF
- Smart Analytics
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS)
- Free MAC client

### Ordering Information

**ELEVI-P5TXIR:** 5 Megapixel Turret, Fixed Lens

### Made in Indonesia

*InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.*