



ELEV-8CHTX4MPKITIP

4-Camera, 4-Megapixel IP Plug & Play Kit

- (4) 4-Megapixel Plug & Play IP Turret Cameras
- (1) 8-Ch NVR
- (4) 60' CAT-5 Cable
- (1) HDMI Cable
- (1) Network Cable
- (1) Video Surveillance Warning Sticker



Easily Add to Your kit with InVid Tech Elevate Series IP Plug & Play Cameras!



Kit Camera

4 Megapixel IP Plug & Play, Outdoor Turret, 82' IR Range, WDR, 12VDC/PoE

Kit Camera Features

- 4 Megapixel (2560 x 1440) Resolution
- Fixed Lens
- H.265/H.265+/H.264/H.264+ Compression
- True Day/Night
- True WDR 120dB
- Smart IR Range up to 82'
- IP66 Weather Resistant
- 12VDC/PoE Operation
- Smart Analytics
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software available to manage your system from your Apple computer

Camera	4 MP IP Kit Camera
Sensor+DSP	OV4689+Hi3516D
Image Sensor	1/3" Progressive scan CMOS Sensor
Min. Illumination	0.01lux(Color), 0lux(IR on)
Lens Mount	M12
Lens	2.8mm Lens @ F1.8: Horizontal FOV: 109°, Vertical FOV: 64°
IR	18pcs SMD LED
IR Range	82' (25m)
Smart IR	Support
Shutter Time	Auto/Manual, 1/3~1/10000s
Day/Night	IR cut filter with auto switch
Wide Dynamic Range	WDR
Digital noise reduction	2D/3D DNR
Compression Standard	
Video Compression	H.264/H.264+/H.265/H.265+
H.264 Codec profile	Base/Main/High profile
H.265 Codec profile	Main profile
Video Bit Rate	11 Kbps~9 Mbps
Triple Streams	Support
Image	
Max. Image Resolution	4MP(2560 × 1440)
Frame Rate	50Hz:25fps 4MP(2560 × 1440),23fps 4MP(2304 × 1728) 25fps 3MP(2048 × 1536),25fps 1080P(1920 × 1080) 25fps 960P(1280 × 960),25fps 720P(1280 × 720) 60Hz:28fps 4MP(2560 × 1440),26fps 4MP(2304 × 1728) 30fps 3MP(2048 × 1536),30fps 1080P(1920 × 1080) 30fps 960P(1280 × 960),30fps 720P(1280 × 720)
Sub Stream	50Hz:25fps D1(704 × 576),25fps CIF(352 × 288) 60Hz:30fps D1(704 × 480),30fps CIF(352 × 240)
Third Stream	50Hz:25fps CIF(352 × 288) 60Hz:30fps CIF(352 × 240)
Image Setting	Brightness/Contrast/Saturation/Hue/Sharpness
BLC	Support
HLC	Support
ROI	Support
Defog	Support
Network	
Network Storage	NAS(NFS/CIFS)
Protocols	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP, RTCP,NTP,IGMP,UPnP,SMTP,UPnP-TM,P2P,Bonjour
Event	Motion Detection, Video Shelter (Tampering)
Smart Functions	Area Intrusion, Line crossing, Object Missing, Unattended Object, Fast Moving
System compatibility	CGI
Security	User authentication,IP address filtering,Video mask
Mobile Surveillance	iPhone, iPad,Android devices
Interface	
Communication interface	1 RJ45 10M / 100M Ethernet Port
General	
Operating Conditions	-30°C ~ 60°C (-22°F ~ 140°F) Humidity 95% or less (non-condensing)
Power Supply	DC12V ± 10%
POE Supply	PoE (802.3af)
Power Consumption	MAX. 6W
Weather Proof	IP66
Dimensions	Ø3.62" × 3.46" (Ø92 x88(H) mm)
Weight	0.88lbs (400g)

Ordering Info:

Kit Part Number: ELEV-8CHTX4MPKITIP



ELEV-8CHTX4MPKITIP

4-Camera, 4-Megapixel IP Plug & Play Kit

(4) 4-Megapixel Plug & Play IP Turret Cameras, (1) 8-Ch NVR, (4) 60' CAT-5 Cable, (1) HDMI Cable, (1) Network Cable, (1) Video Surveillance Warning Sticker



NVR

8 Ch NVR with 8 Plug & Play Ports, 80 Mbps, 1 HD Bay, 4K

Features

- 8 Plug & Play Ports for easy camera setup
- PoE (Power Over Ethernet) available on all ports
- Up to 8 Megapixel Resolution Recording
- 80 Mbps Bit Rate Input
- Supports up to 8 channel simultaneous playback
- Local HDMI main monitor output with 4K Support
- Local VGA main monitor output up to 1080p
- True P2P Connectivity with QR Code Connect
- Multiple video search options including Smart and Thumbnail Search for quick retrieval of footage.
- H.265/H.265+/H.264/H.264+ video compression
- Store and access video storage to the Cloud
- Upgrade your recorder via the Cloud
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software to easily manage your system from your Apple computer

Model	8 Ch Kit NVR
Chipset	Hi3536C
Video & Audio Input	
IP Video Input	8ch
Two Way Talk	1-ch, RCA
Video & Audio Output	
HDMI	4K(3840×2160)/30Hz,1920×1080/60Hz,1440×900/60Hz,1280×1024/60Hz,1280×720/60Hz,1024×768/60Hz
VGA	1920×1080/60Hz,1440×900/60Hz,1280×1024/60Hz,1280×720/60Hz,1024×768/60Hz
Audio Output	1-ch, RCA
Recording	
Compression	H.265+ /H.265/H.264/H.264+
Resolution	8MP / 5MP /4MP / 3MP /1080P /720P /D1/CIF /QCIF
Bit Rate	64Kbps~10Mbps
Playback & Backup	
Playback Resolution	8MP / 5MP /4MP / 3MP /1080P /720P /D1/CIF /QCIF
Decoding Capability	1ch@8MP, 4ch@1080P
Playback Mode	Smart Playback/Normal/Time Division/ Label/ Event/ Log playback
Backup Mode	USB Device/Network/External HDD
Advanced Features	
Smart Detection	Area Intrusion, Line crossing, Object Missing, Unattended Object, Fast Moving
Smart Playback	Area Intrusion, Line crossing, Object Missing, Unattended Object, Fast Moving
Cloud Storage	Support
Cloud Upgrade	Support
Network	
incoming Bandwidth	80Mbps
outgoing Bandwidth	80Mbps
Ethernet	1 RJ-45 10 /100 /1000 Mbps self-adaptive Ethernet interface
Network Function	HTTPs,HTTP,TCP/IP,IPv4,UPnP,UPnP™,RTSP,RTCP,UDP,SMTP,SNMP,Multicast,IGMP,NTP,DHCP,DNS,IP Filter,DDNS,FTP,P2P
Smart Phone	IOS(iPhone, iPad), Android(Phone, Pad)
Hard Disk	
SATA	1 SATA interface
Capacity	Up to 10TB capacity for each HDD
External Interface	
POE Interface	8 independent 10 /100 Mbps PoE Ethernet interfaces
Max Power	24w Per Port, Max 66w Total
USB Interface	Front panel: 1 × USB 2.0 Rear panel: 1 × USB 2.0"
Alarm In	N/A
Alarm Out	N/A
General	
Web Client	User Defined, Max 32 Users
Power Supply	DC48V 2A
Power Consumption	≤15W(without HDD and POE)
Working Environment	32° F ~ 131° (0°C~+55°C)10%~90%RH
Dimension (W×D×H)	9.84" x 9.05" x 1.77" (250 x 230 x 45mm)
Weight	3.96lb (1.8Kg)

Ordering Info:

Kit Part Number: ELEV-8CHTX4MPKITIP