



PAR-P2DRPTZXIR2808

2 Megapixel IP Plug & Play, Outdoor Mini PTZ Dome, 2.8-8mm Motorized Auto-Focus, 65' IR Range, WDR, 350° Rotation, PoE/12VDC


Features

- 2 Megapixel (1920x1080) Resolution
- Motorized Auto-Focus 2.8-8mm Lens
- H.265/H.264/MJPEG Compression
- True Day/Night
- 30 FPS Recording and Live
- True WDR 120dB
- IR Range up to 65'
- IP66 Weather Resistant
- 12VDC/PoE Operation
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Free MAC client software available, through the Paramont NVR, to manage your system from your Apple computer
- Free Central Management Software (CMS), through the Paramont NVR, to manage multiple units & sites from a single platform

Camera	PAR-P2DRPTZXIR2808
Image Sensor	1/2.8" Progressive Scan CMOS
Min. illumination	Color :0.01Lux@(F1.2,AGC ON);B/W: 0 Lux@(IR LED ON)
Day & Night	ICR
Shutter Speed	1/5s-1/20000s
Auto Iris	Fixed
Wide Dynamic Range	T-WDR (96dB)
Digital Noise Reduction	2D/3D
Lens	2.8-8mm Motorized Lens
FOV	90°~45°
IR LED	3pcs
IR Range	Up to 65 Feet
Image	
Video Compression	H.265/H.264/ MJPEG
Bit Rate (CBR/VBR)	Stream1: 500Kbps ~ 12Mbps, Stream2: 100Kbps ~ 6Mbps, Stream3: 100Kbps ~ 3Mbps
Max. Resolution	1920x1080/30fps
Stream	Stream 1 1920x1080 /1280x720 @25/30fps, Stream 2 D1/VGA / /640x 360 / CIF / QVGA @25/60fps, Stream 3 VGA / CIF / QVGA @25/30fps
Image Setting	Rotate Mode, Saturation, Brightness, Contrast ,Sharpness
HLC	Yes
Corridor mode	Yes
ROI	Yes
Defog	Yes
Pan/Tilt	Pan: 0~350° ; Tilt: 0~90°
Pan/Tilt Speed	Pan:0.1~120°/s ; Tilt:0.1~120°/s
Power up Action	Auto restore to previous PTZ and lens status after power failure
Network	
Network Protocols:	IPv4/IPv6,802.1x,HTTP,HTTPS,TCP/IP,UDP/IP,RTSP,DHCP,NTP, RTCP/RTP, PPPoE, SMTP, DNS, UPnP, FTP, APR, SNMP
RTSP Video	Standard RFC2326, Support QuickTime / VLC Player.
Security	User security authentication, Reset, Hardware Watch Dog
Web Language	English, Chinese, Polish, Italian, Portuguese, Spanish, Russian, French, Czech, Hungarian
System Compatibility	ONVIF
Interface	
Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
Reset Button	Built-in
General	
Power Supply	DC12V/PoE
Power Consumption	2.5W(IR LED OFF), 5W IR LED ON
Operating Temperature	-10°C ~ 55°C (14°F ~ 131°F)
Operating Humidity	0% - 90% RH
Ingress Protection	IP66
Approvals	CE / FCC
Product Dimensions	Φ105x73mm
Product Weight	0.99lbs (450g)



Use with the InVid Tech View App
Swipe to View!



Ordering Information

PAR-P2DRPTZXIR2808: 2 Megapixel Mini PTZ Dome, 2.8-8mm