



PAR-P3DRIR 3 Megapixel Network IP Camera, Outdoor Rugged Dome with 65' IR Range, CVBS Output, PoE/DC12V

Features

- 3 Megapixel (2304 x 1296) Resolution
- H.265/H.264/MJPEG Compression
- True Day/Night
- True WDR 120dB
- IR Range up to 65'
- CVBS Video Output
- Audio Input
- IP66 Weather Resistant
- 12VDC/PoE
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software available, through the Paramount NVR, to manage your system from your Apple computer

Camera	
Image Sensor	1/3" CMOS
Image Size	2304 x 1296
Electronic Shutter	1/25s ~ 1/100000s
Auto Iris	Fixed Iris
Min Illumination	0.05 Lux @ F1.2, AGC On; 0 Lux with IR
Lens	3.6mm @ F1.6, Angle of View: 72° (Other Lens Options Available)
Lens Mount	M12
True Day/Night	ICR
Wide Dynamic Range	120dB
BLC	Yes
HLC	Yes
Defogging	Yes
Digital NR	2D/3D DNR
Angle Adjustment	Pan: 0°~240°, Tilt: 0°~68°, Rotation: 0°~220°
Image	
Video Compression	H.265/H.264/MJPEG
H.265 Compression Standard	Main Profile @ Level 4.1 High Tier
Resolution	3 MP (2304 x 1296), 3 MP (2048 x 1536), 1080p (1920x1080), 720p (1280x720), D1, CIF, 480x240
Main Stream	60Hz/30 FPS: 3 MP, 1080p, 720p 50Hz/25 FPS: 3MP, 1080p, 720p
Bit Rate	64 Kbps ~ 8 Mbps
Encode Mode	VBR/CBR
Quality	Five Levels Under VBR; Freely adjustable under CBR
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR: Adjustable through client software or web browser
Audio Compression	G.711A/U
ROI	Each ROI to be configured separately
Interfaces	
Network	RJ45
Audio	MIC-in x 1
Video Output	CVBS Video Output (BNC x 1)
Functions	
Remote Monitoring	IE Browsing, CMS Remote Control
Online Connection	Supports simultaneous monitoring for up to 10-users; Support multi-stream real-time transmission
Network Protocol	TCP/IP, UDP, DHCP, UPnP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
Interface Protocol	ONVIF, GB-T/28181-2011
Storage	Network Remote Storage
Smart Alarm	Motion Alarm
PoE	Yes
IR Distance	65 Feet
Environmental	IP66 Weather Resistant
Housing	IK10 Vandal Resistant
Other	
Power Supply	DC12V/PoE
Power Consumption	<2.5W
IR Consumption	<4W
Operating Environment	-4° ~ 122°F (-20° ~ 50°C), 10-90% Humidity
Dimensions	Ø 4.56 x 3.58 Inches (116x91mm)
Weight	1.33 lbs (605g)

Ordering Information

- PAR-P3DRIR28: 3 Megapixel Dome, 2.8mm
- PAR-P3DRIR36: 3 Megapixel Dome, 3.6mm

3 MEGAPIXEL PLUG & PLAY