




PAR-P4EBXIRA2812

4 Megapixel IP Plug & Play Camera, EXPLOSION Proof Outdoor Bullet, 2.7-13.5mm Motorized Lens, 98' IR Range, WDR, PoE/12VDC

Features

- 4 Megapixel (2592 x 1520) Resolution
- 2.7-13.5mm Motorized Lens
- H.265/H.264/MJPEG Compression
- True Day/Night
- True WDR 120dB
- IR Range up to 98'
- Built-In Mic
- IP67 Weather Resistant
- 12VDC/PoE Operation
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software available, through the Paramont NVR, to manage your system from your Apple computer



Ordering Information

PAR-P4EBXIRA27135: 4 Megapixel Explosion Proof Bullet, 2.7-13.5mm



IPM-EBXIRMOUNT
Bracket

Camera	
Image Sensor	1/3" Progressive Scan CMOS
Effective Pixels	2592(H)×1520(V)
Scanning System	Progressive
Electronic Shutter	1/5-1/20000s
Min. illumination	Color:0.05Lux@(F1.2,AGC ON), B/W:0Lux@(IR LED ON)
S/N Ratio	55dB
IR Range	98 Feet
IR On/Off Control	Auto/ Manual
IR LEDs	3pcs
Lens	
Lens Type	Motorized
Iris	Fixed Iris
Focal Length	2.7~13.5mm
F Number	F1.3
Angle of View	103°~ 34.3°
Focus Control	Motorized
Close Focus Distance	0.2m
Video	
Compression	H.265,H.264,MJPEG
Max. Resolution	4MP(2592×1520)
Streaming Capability	3 Streams
Stream /	Stream1: 2592×1520/2560×1440/2304×1296/ 1920×1080/1280×720 @25/30fps Stream2: D1/VGA/640×360/ CIF/QVGA @25/30fps Stream3: VGA/CIF/QVGA @25/30fps
Frame Rate	
Bit Rate Control	CBR/VBR
Bit Rate	Stream1: 500kbps~12000kbps Stream2: 100kbps~6000kbps Stream3: 100kbps~3000kbps
Day/Night	ICR
Image Enhancement	HLC / Defog / WDR (120dB)
White Balance	Support
Gain Control	Auto/Manual
Noise Reduction	2D/3D DNR
Electronic Image Stabilization(EIS)	Support
Smart IR	Support
Mirror	Support
Region of Interest	Support
Motion Detection	Support
Privacy Masking	Support
Network	
Protocols:	IPv4/IPv6, 802.1x, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, RTCP/RTP, PPPoE, SMTP, DNS, UPnP, FTP, ARP, SNMP
Interoperability	ONVIF
Streaming Method	Unicast
Max. User Access	10 Users
Web Viewer	<IE11, Chrome, Firefox
Management Software	IMS 3.0
Smart Phone	IOS, Android
Intelligence	
IVS	Perimeter, Single Virtual Fences, Double Virtual Fences, Loiter, Multi Loiter, Object Left, Object Removed, Abnormal Speed, Converse, Illegal Parking, Signal Bad
Interface	
Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
Electrical	
Power Supply	DC12V/POE
Power Consumption	2.5W(IR LED OFF), 6.5W IR LED ON
Operating Temperature	Starting Temperature: -30°C ~ 50°C (-22°F ~ 122°F) Working Temperature: -30°C ~ 50°C (-22°F ~ 122°F)
Operating Humidity	Less than 90% RH
Ingress Protection	IP67
Certifications	CE / FCC
Casing	Metal
Dimensions	8.85 x 5.66 x 6.2" (225x144x157.5mm)
Net Weight	15lbs (7Kg)

PAR-EBXIRA2812: Class II, Division 1, Group A

Intrinsic safety (IS) is a protection technique for safe operation of electrical equipment in hazardous areas by limiting the energy available for ignition. In signal and control circuits that can operate with low currents and voltages, the intrinsic safety approach simplifies circuits and reduces installation cost over other protection methods.