



PAR-P4RICS 4 Megapixel IP Plug & Play Box Camera, PoE/ DC12V or 24VAC, CVBS Output, SD Card Slot

Features

- 4 Megapixel (2592 x 1520) Resolution
- H.265/H.264/MJPEG Compression
- True Day/Night
- True WDR 120dB
- CVBS Video Output
- SD Card Local Storage: Up to 128 GB
- Audio Input/Output
- 12VDC/PoE or 24V Option
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software available, through the Paramount NVR, to manage your system from your Apple computer

Camera	
Image Sensor	1/3" CMOS
Image Size	2688 x 1520
Electronic Shutter	1/25s ~ 1/100000s
Auto Iris	DC Drive
Min Illumination	Color: 0.05 Lux @ F1.2, AGC On; B/W: 0.01 Lux @ F1.2, AGC On
Lens	Non-Standard
Lens Mount	C/CS
Day & Night	ICR
Wide Dynamic Range	120dB
BLC	Yes
HLC	Yes
Defogging	Yes
Digital NR	2D/3D DNR
Image	
Video Compression	H.265/H.264/MJPEG
H.265 Compression Standard	Main Profile @ Level 4.1 High Tier
Resolution	4 MP (2592 x 1520), 2K (2560 x 1440), 3 MP (2304 x 1296), 1080p (1920x1080), 720p (1280x720), D1, CIF, 480x240
Main Stream	60Hz/30 FPS: 4MP, 2K, 3 MP, 1080p, 720p 50Hz/25 FPS: 4MP, 2K, 3MP, 1080p, 720p
Bit Rate	64Kbps ~ 10Mbps
Encode Mode	VBR/CBR
Quality	Five Levels Under VBR; Freely adjustable under CBR
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc. Adjustable through client software or web browser
Audio Compression	G.711A/U
ROI	Each ROI to be configured separately
Interfaces	
Network	RJ45
Audio	MIC-in x 1, MIC-out x 1
Video Output	CVBS Video Output (BNC x 1)
Storage Card	Supports SD Card, Up to 128 GB
RS485	Yes
Alarm Input	1 Channel
Alarm Output	1 Channel
Functions	
Remote Monitoring	IE Browsing, CMS Remote Control
Online Connection	Supports simultaneous monitoring for up to 10-users; Support multi-stream real-time transmission
Network Protocol	TCP/IP, UDP, DHCP, UPnP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
Interface Protocol	ONVIF, GB-T/28181-2011
Storage	SD Card Local Storage, Network Remote Storage
Smart Alarm	Motion Alarm, Sensor Alarm
PoE	Yes
Other	
Power Supply	DC12V/PoE
AC Input	AC24V Optional
Power Consumption	<2.5W
Operating Environment	-4° ~ 122°F (-20° ~ 50°C), 10-90% Humidity
Dimensions	2.75 x 5.70 x 2.36 inches (70 x 145 x 60mm)
Weight	0.88 lbs (400g)

Ordering Information

PAR-P4RICS: 4 Megapixel Box Camera, Lens sold separately

4 MEGAPIXEL PLUG & PLAY

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.