



PAR-P5RICS: 5 Megapixel IP Plug & Play, Indoor Box Camera, AC24V/DC12V/PoE

Features

- 5MP (2592 × 1944) H.265 full real time coding
- Max.resolution: 2592 × 1944; ICR auto switch, true day / night
- 3D DNR, true WDR, HLC, BLC, Smart IR and ROI coding
- One CVBS output
- 1CH audio input and 1CH audio output; Hardware reset
- Support SD card slot, up to 128GB
- 1CH alarm input; 1CH alarm output; RS485
- AC24V/DC12V/PoE power supply
- Support smart phone, iPad, remote monitoring
- Support three streams
- P2P function optional
- Support face detection
- Smart analytics (optional): object removal detection, abnormal, video signal detection, line crossing detection, region intrusion, detection, people intrusion detection, people counting detection, crowd density detection, etc.

Camera	PAR-P5RICS
Image Sensor	1/2.5" CMOS
Image Size	2592×1944
Electronic Shutter	1/25s ~ 1/100000s
Iris Type	Auto Iris, DC Drive
Min Illumination	0.036 lux @F2.0, AGC ON; 0.009 lux 0.013 lux @ F1.2, AGC ON; 0.003 lux @F1.2, AGC ON @F2.0, AGC ON
Lens Mount	C/CS
Wide Dynamic Range	120dB
BLC	Yes
HLC	Yes
Defog	Yes
Digital NR	2D/3D DNR
Image	
Video Compression	H.265/H.264/MJPEG
H.265 Compression Standard	Baseline Profile/Main Profile/High Profile
Resolution	5MP (2592 × 1944), 3MP (2304 × 1296), 1080P (1920 × 1080), 720P (1280 × 720), D1, CIF, 480 × 240, 4MP (2592 × 1520), 2K (2560 × 1440),
Main Stream	60Hz : 5MP(1~30fps)/ 3MP(1~30fps)/ 1080P(1~30fps)/ 720P(1~30fps) 50Hz : 5MP(1~25fps)/ 4MP 1~25fps / 2K 1~25fps / 3MP 1~25fps / 1080P 1~25fps / 720P 1~25fps 4MP(1~30fps)/ 2K(1~30fps)/
Sub Stream	60Hz: 720P(1~15 FPS)/ D1(1~30FPS)/ CIF(1~30FPS) 50Hz: 720P(1~15FPS)/ D1(1~25FPS)/ CIF(1~25FPS)
Third Stream	60Hz : D1/CIF/480 × 240 (1~30fps); 50Hz: D1/CIF/480× 240 (1~25fps)
Bit Rate	128Kbps ~ 10Mbps
Bit Rate Type	VBR/CBR
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR: Adjustable through client software or web browser
Audio Compression	G.711A/U
ROI	Each ROI to be configured separately
Interfaces	
Network	RJ45
Video Output	CVBS Output (BNC x 1)
Audio	1 CH Audio Input; 1 CH Audio Output
Storage	SD Card Slot; Up To 128 GB
Hardware Reset	Yes
Alarm	1 CH Alarm Input; 1 CH Alarm Output
RS 485	Yes
Functions	
Remote Monitoring	Web Browsing, CMS Remote Control
Online Connection	Supports simultaneous monitoring for up to 10-users; Support multi-stream real-time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, 802.1x, UPnP, HTTPS, QoS
Interface Protocol	ONVIF, GB-T/28181-2011
Storage	Network Remote Storage, SD Card Storage
Smart Alarm	Motion Detection, Sensor Alarm, SD Card Error, SD Card Full, IP Conflict, Network Disconnection
Intelligent Analytics	Face Detection (Object Removal Detection, Regional Intrusion Detection, Abnormal Video Detection, Line Crossing Detection, People Intrusion, People Counting And Crowd Density Detection Optional)
General Function	Watermark, IP Address Filtering, Video Mask, Heartbeat, Password Protection.
PoE	Yes
Other	
Power Supply	AC24V/DC12V/PoE
Power Consumption	< 4W
Operating Environment	-22°F~ 104°F(-30°C ~ 40°C) Humidity: Less Than 95% (Non-condensing)
Dimensions (mm)	138.4 x 70 x 60.5
Weight (net)	Approx. 0.4KG
Installation	Wall Mounting

Ordering Information

PAR-P5RICS: 5 Megapixel, Outdoor Box Camera