



PAR-ALL5DRPTZXIRA2808

5 Megapixel All-in-One Outdoor Rugged Mini PTZ Dome
2.8-8mm Motorized Auto-Focus Lens, 350° Rotation, 12VDC

Features

- 5 Megapixel Resolution (2560 x 1920)
- All-in-One Technology (TVI/AHD/CVI/Analog 960h)
- Motorized Auto-Focus 2.8-8mm Lens
- 350° Rotation
- True Day/Night
- 65' IR Range
- Up The Cable (UTC) Function
- 12VDC Operation

| | |
|-------------------------|-----------------------------------|
| Camera | PAR-ALL5DRPTZXIRA2808 |
| Image Sensor | 1/2.9" CMOS |
| Signal System | PAL/NTSC |
| Min. Illumination | Color 0.01Lux(AGC ON);IR ON 0 Lux |
| SN | ≥50dB |
| Day & Night | ICR |
| Shutter Speed | Auto |
| Digital Noise Reduction | 2D |
| Lens | 2.8-8mm Auto-Focus Motorized Lens |
| FOV | 89° ~ 35° |
| IR LED | 2pcs |
| IR Wavelength | 850nm |
| IR Range | 65' |
| Image | |
| Effective Resolution | 2560×1920 |
| Frame | 5MP@20fps |
| White Balance | Auto |
| Rotation | Pan 350°, Tilt 90° |
| Gain | Auto |
| Light Compensation | Auto |
| Video Output | |
| Max. Distance | 75-5 300m |
| Video Output | AHD/TVI/CVI/CVBS |
| General | |
| Power Supply | DC12V±10% |
| Power Consumption | <6W |
| Operating Temperature | 14°F ~ 122°F (-10°C~+50°C) |
| Operating Humidity | 0% - 85% RH |
| Ingress Protection | IP66 |
| Approvals | CE / FCC |
| Material | Aluminum Alloy |
| Product Dimensions | Ø 4 x 3 in (105×75 mm) |
| Product Weight | 0.6 lbs (350g) |

Ordering Information

PAR-ALL5DRPTZXIRA2808: 5 Megapixel, Motorized 2.8-12mm Lens

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.