



SN1A-16X16T

16 Channel NVR with 16 Plug and Play Ports,
Body Temperature Detection

- 16 Channel with 16 Plug & Play Ports for easy camera setup
- PoE (Power Over Ethernet) available on all ports
- Up to 8 Megapixel Resolution Recording
- 160 Mbs Bit Rate Input
- Works with ONVIF or other supported IP cameras
- Local HDMI main monitor output with 4K Support
- Local VGA main monitor output up to 1080p
- H.265/H.265+/H.264/H.264+ video compression
- Free Central Management Software (CMS)



System	
Main Processor	Dual-core embedded processor
Operating System	Embedded LINUX
Video and Audio	
IP Camera Input	16 Channel
Audio I/O	1/1, RCA
Two-way Talk	Yes
Display	
Interface	1 HDMI, 1 VGA
Resolution	HDMI: 3840×2160,1920×1080,1440×900, 1280×1024, VGA: 1920×1080, 1280×1024, 1280×720
Decoding Capacity	1ch 8MP/4ch 1080P@30fps
Multi-screen Display	1/4/9/16
Recording	
Compression	H.265+/ H.265/H.264+/H.264
Resolution	8MP/6MP/5MP/4MP/3MP/1080P/720P/ D1&etc.
Record Rate	160Mbps
Bit Rate	100Kbps ~ 6Mbps Per Channel
Record Mode	Manual, Schedule (Regular, Continuous), Motion Detection, Video Loss, Camera Tamper, Alarm in
Record Interval	Post-record: 30 ~ 60 sec
Video Detection and Alarm	
Trigger Events	Recording, Buzzer, Push message, Pop up message.
Video Detection	Motion Detection, Video Loss, Camera Tamper
Alarm In/Out	8/2
Playback and Backup	
Sync Playback	16/9/4/1
Search Mode	Time /Date, Alarm, Picture grid, Event
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Shuffle, Backup Selection, Digital Zoom
Backup Mode	USB Device
Network	
Network Function	HTTP, HTTPS, TCP/IP, IPv4, UPnP, UDP, RTSP, SMTP, NTP, DNS, DHCP, P2P, IP Filter, DDNS, 802.1X, SNMP
Max. User	Access 9 users
Smart Phone	iPhone, iPad, Android
Interoperability	ONVIF, SDK, CGI
Storage	
Internal HDD	2 SATA Ports, up to 8TB for each HDD
eSATA	N/A
Interface	
Interface	1 RJ-45 port (10/100/1000Mbps)
PoE Interface	16ch 100Mbps, IEEE 802.3af
PoE Max Power	120W
USB	2 ports (USB 2.0 x2)
General	
Power Supply	AC100~240V
Power Consumption	< 5W (without HDD)
Operating Conditions	14 °F ~ 122 °F (-10 °C ~ 50 °C)
Storage Conditions	Less than 90% RH
Certifications	CE/FCC
Dimensions	14.64" x 12.22" x 1.83" (372×310.5×46.5mm)
Net Weight	4.62lb (2.1kg) No disk

Ordering Information

SN1A-16X16T: 16 Ch NVR with body temp features

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.