



UD3A-32

32 Ch TVI/Analog Universal Port Recorder (2 MP), with 8 Bonus IP Ch (2 MP), Up to 40 cameras total, 4 HD Bays

- 32 Channel Universal Port 2MP DVR (TVI/AHD/Analog)
- 8 Bonus IP Channel - Up To 2 Megapixel
- H.265+/H.265/H.264+/H.264 Video Compression (H.265+/H.264+ Only Compatible with Ultra Cameras)
- Simultaneous HDMI/VGA up to 1080p Resolution
- CVBS Main or Spot Monitor
- Supports up to 16 Channel Simultaneous Playback
- Multiple video search options including Smart Search and Sub-Periods for quick retrieval of footage.
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software to easily manage your system from your Apple computer

Model Number	UD3A-32
Video compression	H.265+/H.265/H.264+/H.264 Video Compression (H.265+/H.264+ Only Compatible with Ultra Cameras)
HD-TV/ Analog Video Input	32 Ch. BNC input, 1Vp-p, 75Ω
Supported camera types	720P25, 720P30, 720P50, 720P60, 1080P25, 1080P30, CVBS
Audio compression	G.711u
Audio Input/ Two-way audio in	4 Ch. input/1 Ch. two way audio RCA (2.0 Vp-p, 1kΩ)
Video output	1 HDMI, 1 VGA, 1 CVBS, up to 1920 x 1080
Encoding resolution	Main stream: 1080P (non-real-time) / 720P / VGA / WD1 / 4CIF / CIF, Sub-stream: WD1(non-real-time) / 4CIF(non-real-time) / CIF / QCIF / QVGA
Frame rate	Main stream: 1/16 fps ~ Real time frame rate Sub-stream: 1/16 fps ~ Real time frame rate
Video bitrate	32 Kbps to 6 Mbps
Audio output	1 Ch., RCA (Linear, 1KΩ, for VGA output and CVBS output)
Audio bitrate	64 Kbps
Dual-stream	Support
Stream type	Video & Audio
Synchronous playback	16 Ch.
Playback resolution	1080P / 720P / VGA / WD1 / 4CIF / CIF / QVGA / QCIF
Remote connections	128
Type	4 SATA interfaces for 4 HDDs; 1 eSATA interface
Network protocols	TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS
Capacity	Up to 10 TB capacity for each disk
Network interface	1; 10M / 100M / 1000M self-adaptive Ethernet interface
Serial interface	RS-232, RS-485, Keyboard
USB Interface	3 x USB2.0
Power	100 ~ 240VAC, 47 ~ 63HZ, <=65W
Working temperature	-10 °C ~+55 °C (14 °F ~ 131 °F)
Working humidity	10% ~ 90%
Chassis	19-inch rack-mounted 1.5U chassis
Dimensions (W x D x H)	17.5 W x 15.3 D x 2.7 H
Weight (Without hard disks)	17.6 lbs
Working humidity	10% ~ 90%
Chassis	19-inch rack-mounted 1.5U chassis
Dimensions (W x D x H)	445 x 390 x 70 mm (17.5 x 15.3 x 2.7 inch)
Weight (Without disks)	17.6lbs

Ordering Information

UD3A-32/2TB: 32 Ch DVR with, 2 TB

Available with various configurations 0-56TB