



ULT-P2DRIR

2 Megapixel IP Plug & Play, Outdoor Vandal Dome, 100' IR Range (12VDC/PoE Operation)

Features

- 2 Megapixel (1920 x 1080) Resolution
- Fixed Lens
- H.264/MJPEG
- True Day/Night
- D-WDR
- 100' IR Range
- IK10 Vandal Resistant
- IP66 Weather Resistant
- ONVIF
- 12VDC/PoE Operation
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Mac Client

Model Number	ULT-P2DRIR
Image Sensor	1/3 progressive scan CMOS
Min. illumination	0.01 lux @ F1.2, AGC ON, 0 lux with IR
Shutter time	1/30s ~ 1/100,000s
Lens	2.8mm @ F2.0, angle of view 52° (6.0mm optional)
Lens mount	M12
Day & night	ICR
Wide Dynamic Range	DWDR
Video compression	H.264 / MJPEG
Bit rate	32 Kbps ~ 16 Mbps
Dual stream	Yes
Max. image resolution	2MP CMOS, (1920 x 1080)
Frame rate	60 Hz 30 fps (1920 x 1080), 30 fps (1280 x 720)
Image settings	Saturation, brightness, contrast adjustable through client software or web browser
Network storage	NAS
Alarm trigger	Motion detection, tampering alarm, network disconnect, IP address conflict, storage exception
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
System Compatibility	ONVIF, PSIA, CGI
General functionalities	Flickerless, heartbeat, mirror, user authentication, video mask, watermark
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Operating conditions	-22 °F ~ 140 °F (-30 °C ~ 60 °C) humidity 90% or less (non-condensing)
Power supply	12 VDC +/- 10%, PoE (802.3af)
Power consumption	7W Max.
Impact protection	IK10
IR range	up to 100 ft
Dimensions	Ø 4.4 x 3.2 (140 x 92mm)
Weight	1.32lbs (600g)

Ordering Information

ULT-P2DRIR28: 2 Megapixel Dome, 2.8 mm Lens

ULT-P2DRIR6: 2 Megapixel Dome, 6 mm Lens