



ULT-P4BIRN

4 Megapixel IP Plug & Play Bullet, 2.8mm, WDR, 100' IR Range, PoE/DC12V

Features

- 4 Megapixel (2688 x 1520) Resolution
- Fixed Lens
- H.265+/H.265/H.264+/H.264/MJPEG Compression
- True Day/Night
- True WDR 120dB
- 100' IR Range
- IP67 Weatherproof
- 12VDC/PoE Operation
- ONVIF
- SD Slot for Local Storage: Up to 128GB
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free Mac Client

Model Number	ULT-P4BIRN
Image Sensor	1/3" progressive scan CMOS
Min. illumination	0.01 lux @ (F1.2, AGC ON), 0 lux with IR
Shutter time	1/30s ~ 1/100,000s
Lens	4mm @ F2.0 Angle of view: 78.7°
Day & night	IR cut filter with auto switch
Digital noise reduction	3D DNR
Wide dynamic range	True WDR
Video compression	H.264 / H.264+ / MJPEG / H.265 / H.265+
Max. image resolution	2688 x 1520
Frame rate	30fps (2688 x 1520)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
Storage	NAS, on board 128GB SD card slot.
Alarm trigger	motion detection, tampering alarm, network disconnect, IP address conflict, storage exception
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
Security	User Authentication, reset button, flickerless, dual stream, heartbeat, mirror, watermark
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Operating conditions	-22 °F ~ 140 °F (-30 °C ~ 60 °C) humidity 95% or less (non-condensing)
Power supply	12 VDC +/- 10%, PoE (802.3af)
Power consumption	Max. 6W
Ratings	IP67
IR range	UP to 100ft
Dimensions	Φ2.76" × 6.1"
Weight	0.9 lbs

Ordering Information

ULT-P4BIR28N: 4 Megapixel, 2.8mm

ULT-P4BIR4N: 4 Megapixel, 4.0mm

ULT-P4BIR6N: 4 Megapixel, 6.0mm

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.

4 MEGAPIXEL PLUG & PLAY