



ULT-P4DRIRM2812N

4 Megapixel IP Plug & Play, Outdoor Vandal Dome, 2.8-12mm Motorized, 90' IR Range, CVBS Output, WDR, SD Card Slot, Poe/DC12V, White Housing

Features

- 4 Megapixel (2688 x 1520) Resolution
- 2.8-12mm Motorized Varifocal Lens
- H.265+/H.265/H.264+/H.264/MJPEG Compression
- 30 FPS Recording and Live
- True Day/Night
- True WDR 120dB
- 90' IR Range
- IP67 Weatherproof
- 12VDC/PoE Operation
- ONVIF
- SD Slot for Local Storage: Up to 128GB
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free Mac Client

Model Number	ULT-P4DRIRM2812N
Image Sensor	1/3" progressive scan CMOS
Min. illumination	0.01 lux @ (F1.2, AGC ON), 0 lux with IR
Shutter time	1/30s ~ 1/100,000s
Lens	2.8 ~ 12mm @ F1.4, Angle of view: 88° ~ 29°
Day & night	ICR
Digital noise reduction	3D DNR
Wide dynamic range	120dB
Angle adjustment	Pan: 0° ~ 355°, tilt 0° ~ 75°
Video compression	H.264 / MJPEG / H.264+ / H.265 / H.265+
Max. image resolution	2688 x 1520
Frame rate	30fps (2688 x 1520)
Audio	1/1
Network Storage	NAS
Alarm	1/1
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
System Compatibility	ONVIF, PSIA, CGI
General functionalities	User authentication, watermark, dual stream
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
On Board Storage	Built-in Micro SD slot, up to 128 GB
Operating conditions	-22 °F ~ 140 °F (-30 °C ~ 60 °C) humidity 95% or less (non-condensing)
Power supply	12 VDC +/- 10%, PoE (802.3af)
Power consumption	Max. 5.5W
Impact Protection	IK10
Ingress Protection Level	IP67
IR range	Up to 90ft
Dimensions	Ø 6.04" x 5.24" (Ø 140 x 99.9 mm)
Weight	2.84lbs

Ordering Information

ULT-P4DRIRM2812N: 4 Megapixel Dome, 2.8-12mm Motorized Lens, White Housing

ULT-P4DRIRM2812BN: 4 Megapixel Dome, 2.8-12mm Motorized Lens, Black Housing

4 MEGAPIXEL PLUG & PLAY