



ULT-P4LIRN

4 Megapixel IP Plug & Play, Mini Outdoor Low Profile

Features

- 4 Megapixel (2688 x 1520) Resolution
- Fixed Lens
- H.265+/H.265/H.264+/H.264/MJPEG Compression
- True Day/Night
- True WDR 120dB
- 30' EXIR Range
- Audio Input/Output: Built-in Mic
- IP66 Weather Resistant
- 12VDC/PoE Operation
- ONVIF
- SD Slot for Local Storage: Up to 128GB
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free Mac Client

Model Number	ULT-P4LIR28N
Image sensor	1/2.9" progressive scan CMOS
Min. illumination	0.01lux @ F1.2, AGC on, 0 lux with IR
Shutter time	1/30s ~ 1/100,000s
Lens	2.8mm @ F2.0
Day & night	ICR
Digital noise reduction	3D DNR
Wide Dynamic Range	True WDR, 120db
Video compression	H.264 / MJPEG / H.264+ / H.265 / H.265+
Alarm	1/1
Audio	1/1
Max. image resolution	2688 x 1520
Frame rate	30fps (2688 x 1520)
Alarm trigger	Motion detection, tampering alarm, network disconnect, IP address conflict, storage exception, storage error
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
System compatibility	ONVIF, PSIA, CGI
General functionalities	Flickerless, dual stream, heartbeat, mirror, user authentication, video mask, watermark
Communication interface	1 RJ45 10M / 100M ethernet port
On-board storage	Built-in Micro SD card slot, up to 128 GB
Operating conditions	-22 °F ~ 140 °F (-30 °C ~ 60 °C), humidity 95% or less (non-condensing)
Power supply	DC12V ± 10%, PoE (802.3af)
Power consumption	Max. 9.5W
Ingress protection level	IP66, IK08
IR range	Up to 30ft
Dimensions	4.33 x 2.22
Weight	250g (0.88 lbs)

Ordering Information

- ULT-P4LIR28N:** 4 Megapixel Low Profile, 2.8mm, White Housing
- ULT-P4LIR4N:** 4 Megapixel Low Profile, 4.0mm, White Housing
- ULT-P4LIR6N:** 4 Megapixel Low Profile, 6.0mm, White Housing
- ULT-P4LIR28BN:** 4 Megapixel Low Profile, 2.8mm, Black Housing