



ULT-P5DRIRA

5 Megapixel IP Plug & Play, Outdoor Rugged Dome, 90' IR Range, WDR, Audio Input/Output, SD Card Slot, PoE/DC12V

Features

- 5 Megapixel (2944x1656) Resolution
- Fixed Lens
- H.265+/H.265/H.264+/H.264/MJPEG Compression (H.265+/H.264+ only for use with Ultra Cameras)
- True Day/Night
- True WDR 120dB
- 100' Smart EXIR Range
- Audio Input/Output
- IK10 Vandal Resistant
- IP67 Weather Resistant
- 12VDC/PoE Operation
- ONVIF
- SD/SDHC/SDXC Card slot up to 128 GB
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free Mac Client

Mounting Options



Ordering Information

ULT-P5DRIRA28: 5 Megapixel Dome, with audio, 2.8mm

ULT-P5DRIRA4: 5 Megapixel Dome, with audio, 4mm

ULT-P5DRIRA6: 5 Megapixel Dome, with audio, 6mm

| | |
|-------------------------|---|
| Model Number | ULT-P5DRIRA |
| Image Sensor | 1/2.9" progressive scan CMOS |
| Min. illumination | 0.01 lux @ (F1.2, AGC ON), 0 lux with IR |
| Shutter time | 1/3s ~ 1/100,000s |
| Lens | 2.8mm @ F1.2, angle of view: 90° (4mm/6mm options available) |
| Angle adjustment | Pan: -90° ~ 90°, tilt 0° ~ 75°, Rotation: 0-355° |
| Digital noise reduction | 3D DNR |
| Wide dynamic range | True WDR |
| Day & night | ICR |
| Video compression | H.264 / H.264+ / MJPEG / H.265 / H.265+ |
| Dual stream | Yes |
| Audio | 1/1 |
| Alarm | 1/1 |
| Max. image resolution | 2944x1656 |
| Frame rate | 20fps (2944x1656), 30fps (2560x1440, 2048x1536, 1920x1080, 1280x720) |
| Image settings | Saturation, brightness, contrast, sharpness adjustable through client software or web browser |
| BLC | Yes, zone configurable |
| On Board Storage | Micro SD slot, up to 128GB |
| Alarm trigger | Motion detection, tampering alarm |
| Protocols | TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos |
| System compatibility | ONVIF, PSIA, CGI |
| General functionalities | User authentication, watermark |
| Communication interface | 1 RJ45 10M / 100M Ethernet interface |
| Operating conditions | -30°C ~ 60°C (-22°F ~ 140°F) humidity 90% or less (non-condensing) |
| Power supply | 12 VDC +/- 10%, PoE (802.3af) |
| Power consumption | Max. 9W |
| Ratings | IP67 / IK10 |
| IR range | Up to 100ft |
| Dimensions | Ø 4.4"x3.2" |
| Weight | 1.1 lbs (500g) |