



ULT-P5DRIR

5 Megapixel IP Plug & Play, Outdoor Rugged Dome, 100' IR Range, WDR, SD Card Slot, PoE/DC12V

Features

- 5 Megapixel (2560 x 1920) Resolution
- Fixed Lens
- H.265+/H.265/H.264+/H.264/MJPEG Compression (H.265+/H.264+ only for use with Ultra Cameras)
- True Day/Night
- True WDR 120dB
- 100' Smart EXIR Range
- IK10 Vandal Resistant
- IP67 Weather Resistant
- 12VDC/PoE Operation
- ONVIF
- SD/SDHC/SDXC Card slot up to 128 GB
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free Mac Client

Mounting Options



IUM-DRJB1:
Small Dome
Junction Box #1



IUM-BRCM1*
Corner Mount #1



IUM-DRWM3
Wall Mount #3



IUM-DRWM1:
Small Dome
Wall Mount #1



IUM-BRPM1*
Pole Mount #1



IUM-DRPM1:
Pendant Mount
#1

Ordering Information

ULT-P5DRIR28: 5 Megapixel Dome, 2.8mm

ULT-P5DRIR4: 5 Megapixel Dome, 4mm

ULT-P5DRIR6: 5 Megapixel Dome, 6mm

Model Number	ULT-P5DRIR
Image Sensor	1/2.9" progressive scan CMOS
Min. illumination	0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter time	1/3s ~ 1/100,000s
Lens	4mm @ F1.2, angle of view: 63.5° (2.8, 6mm optional)
Angle adjustment	Pan:0° ~ 355°, tilt 0° ~ 75°, Rotation: 0°~ 355°
Digital noise reduction	3D DNR
Wide dynamic range	True WDR
Day & night	ICR
Video compression	H.264 / H.265 / MJPEG
Dual stream	Yes
Max. image resolution	2560x1920
Frame rate	20fps(2560x1920), 30fps(2560x1440, 2048x1536, 1920x1080, 1280x720)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
BLC	Yes, zone configurable
On Board Storage	Micro SD slot, up to 128GB
Alarm trigger	Motion detection, tampering alarm
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
System compatibility	ONVIF(PROFILE S, PROFILE G), PSIA, CGI, ISAPI
General functionalities	One-key Reset, Anti-Flicker, Heartbeat, Mirror, Password Protection, Privacy Mask, Watermark, IP Address Filter
Communication interface	1 RJ45 10M / 100M self-adaptive Ethernet interface
Operating conditions	-30°C ~ 60°C (-22°F ~ 140°F) humidity 95% or less (non-condensing)
Power supply	12 VDC +/- 25%, PoE (802.3af)
Power consumption	12 VDC, 6.2W; PoE(802.3af, class 3), 9 W
Ratings	IP67 / IK10
IR range	Up to 100ft
Dimensions	Ø 4.4"x3.2"
Weight	1.1 lbs (500g)