



ULT-C2PTZ23R HD-TVI 1080P Interior 23x PTZ Camera

Features

- 2 Megapixel (1920 x 1080) Resolution
- 23x Optical Zoom (16x Digital Zoom)
- Digital WDR
- CVBS Video Output
- Recessed Indoor Housing Only
- Operates to -22° F

Model Number	ULT-C2PTZ23R
Image Sensor	1/3" CMOS
Effective Pixel	1920x1080
Frame Rate	50Hz:25fps(1280x1080) 60Hz:30fps(1280x1080)
Min. Illumination	Color: 0.05Lux@(F1.6,AGC ON), B/W: 0.005Lux@(F1.6,AGC ON)
Max Image Resolution	1080p
Wide Dynamic Range	DWDR
Shutter Time	NTSC: 1-1/10,000s
Focal Length	4-92mm, 23X
Optical Zoom	23X
Digital Zoom	16x
HD Video Output	1 HD-TVI out - 1 Analog
White Balance	Auto / Manual / ATW / Indoor / Outdoor
AGC	Auto / Manual
S / N Ratio	≥ 50dB
3D DNR	Support
Backlight Compensation	Support
Day & Night	IR Cut Filter
Privacy Mask	8 privacy masks programmable; a maximum of 8 zones can be masked simultaneously on the same video screen
Focus Model	Auto / Semiautomatic / Manual
Zoom Speed	Approx.3.0s(Optical Wide-Tele)
Angle of View	49-2.2 degree(Wide-Tele)
Min. Working Distance	10-1000mm (Wide-Tele)
Aperture	F1.6-F3.7
Park Action	Preset / Patrol / Pattern / Pan scan / Tilt scan / Frame Scan / Random scan / Panorama scan
Scheduled Task	Preset / Patrol / Pattern / Pan scan / Tilt scan / Frame Scan / Random scan / Panorama scan
Pan Range	360° endless
Pan Speed	Pan Manual Speed: 0.1°-250°/s, Pan Preset Speed: 300°/s
Tilt Range	-5°-90° (Auto Flip)
Tilt Speed	Tilt Manual Speed: 0.1°-150°/s, Tilt Preset Speed: 200°/s
Proportional Zoom	Rotation speed can be adjusted automatically according to zoom multiples
Number of Preset	256
Patrol	8 patrols, up to 32 presets per patrol
Pattern	4 patterns, with the total recording time not less than 10 minutes
Power-off Memor	Support
PTZ Position Display	On / Off
Preset Freezing	Support
Monitor Output	1 turbo HD1080p output 1.0V(p-p) / 75Ω, NTSC (or PAL) composite, BNC
RS-485 communication diagnosis	Pelco-P, Pelco-D, OSD (UTC control) via DVR
RS-485 Interface	Half-duplex mode Self-adaptive HIKVISION, Pelco-P, Pelco-D protocol
UTC function	*Need UTC controller if DVR don't support UTC function
Menu Language	English, Chinese
Power	24VAC, Max. 12W
Operating Temperature	-22°F-149°F (-30 °C-65°C)
Dimension	φ9.65" x9.29"
Weight	6.61lbs

Ordering Information

ULT-C2PTZ23R: 2 Megapixel TVI PTZ Indoor Recessed, 23x Zoom

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.

2 MEGAPIXEL | 1080p