



ULT-C2BIR2812 2 Megapixel/1080p TVI Outdoor Bullet, 2.8-12mm, 120' IR Range, Dual Voltage

Features

- 2 Megapixel (1920 x 1080) Resolution
- Varifocal 2.8-12mm Lens
- True Day/Night
- 120' IR Range
- Up The Cable (UTC) Function
- Withstand up to -40° Operation
- Dual Voltage

Model Number	ULT-C2BIR2812
Image Sensor	1 / 3" Progressive Scan CMOS
Signal System	PAL / NTSC
Effective Pixels	1920(H)*1080(V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR 0.014 Lux @ (F1.4,AGC ON),0 Lux with IR
Shutter Speed	1/25 s to 1/50,000s
Lens (Angle of View)	2.8 – 12 mm @ F1.4 (102° – 35°)
Auto Iris	Yes
Angle Adjustment	Pan: 0 – 360°, Tilt: 0 – 90°
Day & Night	IR Cut Filter with Auto Switch
Wide Dynamic Range	DWDR
Synchronization	Internal synchronization
Video Frame Rate	1080p @ 30fps
HD Video Output	1 HD-TVl output up to 1200ft with RG59U 95%
S / N Ratio	More than 52dB
Scene	Indoor, Outdoor, Indoor1, LOW-LIGHT
Camera ID	On/off (15 characters, position programmable)
AGC	Support
D/N Mode	Color/BW/EXT
White Balance	ATW, AWC-SET, Indoor, Outdoor, Manual
Privacy Mask	On / Off, maximum 2 zones
Motion Detection	On / Off, maximum 4 zones
BLC	Support
Anti-flicker	On/off
Language	English, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and Arabic
Function	Digital noise reduction, Digital zoom(62x)
Working Temperature / Humidity	-4 °F – 140 °F (-20 °C – 60 °C)
Humidity	Humidity 90% or less (non-condensing)
Power Supply	Dual Volt: 12 VDC, 24 VAC
Power Consumption	Max. 5W
Housing	IP66
IR Range	Up to 120 ft
Communication	OSD (UTC Control) via DVR
Dimensions	3.62 x 3.34 x 10.6 in (91.9 x 84.8 x 269.2mm)
Weight	1.52lbs (689g)

Ordering Information

ULT-C2BIR2812: 2 Megapixel Bullet, 2.8-12mm

2 MEGAPIXEL | 1080p

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.